

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Elder &amp; Gile, Contract #31 dated April, 1853 ----- Set ¼ Sec. post, from which     A Y.Oak 20" dia. bears N.69°E., 64 lks.     A W.Oak 18" dia. bears S.25°W., 93 lks.</p>
<p>F. J. Cole, Deputy - Wit. Miles Parks - May 6, 1915 - F.B. 37 Page 38 ----- Rock set for Cor. from which original tree bears S.25°W., 93 lks. Marked new trees:     A B.Oak 6" dia. bears N.20°E., 21 lks.     A B.Oak 6" dia. bears S.53°W., 20 lks.</p>
<p>Richardson, Godfrey and Kershner - March 10, 1946 (No source reference found) C.S. File 39/50 pg 42 (added 8/20/2024) ----- Set from split rock with X on top, trees gone, stumps check for bearing and distance.     7" Oak bears N.25°E., 73.4 ft.     8" W.Oak N.8¼°E., 102.8 ft.</p>
<p>J.W. Byron, Deputy Co. Surveyor - R.Irving; J.Fee; Done for Darley Ware - May 24, 1954 - C.S. File 46/6 ----- Found - Split rock with cross on top, Trees have been cut. Scribing on both trees visible &amp; the check for bearing &amp; distance. Set - A 1" I.Pipe with brass cap mkd. County Surveyor's Office T26S, R6W 25 36 ¼S 1954. Blazed &amp; Scribed:     6" W.Oak N.34½°E., 63.4 ft. mkd. ¼S 25 CS BT.     4" W.Oak S.80°E., 31.5 ft. mkd. ¼ S36 CS BT.</p>
<p>Fd. OK July 1964. Cor. Approx. 150' W. of fence line along W. R/W line along Hwy. #5.</p>
<p>Victor McLind For: L. Cornish, May 1977 - M 60-16 ----- Brass cap not found. Reset corner from BTs:     A 10" W.Oak bears N.34½°E., 63.4 ft.     A 8" W.Oak bears S.80°E., 31.5 ft. Set - 5/8" x 30" Iron rod at corner.</p>
<p>Fd. 5/8" IR R. Quimby - 2009-0017</p>