

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NE Cor Gillham DLC #46

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

| |
|---|
| <p>Original - J. A. Burnett, under Contract #75 dated Nov. 22 1856</p> <p>-----</p> <p>The NE cor. of C. 46, at a point 24.00 E. and 76 lks. S. of sec. cor. of secs. 13, and 24; from which A B.Oak 18" dia., bears S.35°W., 312 lks.</p> |
| <p>WF Briggs, Feb. 3, 1892 - Vol. 1 Pgs. 208-09; Field Bk 4 Pg18</p> <p>-----</p> <p>Marked the following BT: A B.Oak 30" dia., bears S.35°W., 200 lks.</p> |
| <p>Doug. County Surveyors Office - James W. Byron, Deputy County Surveyor - Milo Godfrey; Clete Putnam - May 1960 - C.S. File 49/129-2</p> <p>-----</p> <p>Note - NE Corner of DLC is close to new house, so I set Witness Corner 88 ft. West. Set Brass cap at Wit corner mkd: Wit. Co. 88' East to NE Cor. DLC 46 T26S R7W</p> <p>This corner set from BT., now 48" B.Oak, recorded by Briggs, in 1892, S.35°W., 132.0 ft. I open and find good scribing. New BTs- 34" W.Oak bears N.69°W., 5.0 ft. scribed W C NE DLC CS BT. 14" R.Fir bears S.5½°W., 34.5 ft. scribed WC NE DLC 46 CS BT.</p> |
| <p>Doug. County Surveyors Office - L.E. Monrean, Nov. 17, 1975 C.S. File 57/39-13</p> <p>-----</p> <p>Found - DCS0 brass cap stamped 1960, properly marked. 34" now 35" dia., W.Oak bears N.69°W., 5.0 ft. has good blaze, tagged. 14" now 17" dia. R.Fir bears S.4½°W., 34.5 ft. (Rec. S.5½°W) Tree is dead and will be removed. B. Oak bearing tree not found.</p> <p>New BT - R.Fir 23" dia., bears S.18½°E., 57.2 ft. scribed "WC NE DLC #46 DC BT"</p> |
| <p>Doug. County Surveyors Office - Larry E. Monrean, Deputy; J.R. Lundeen - June 10, 1983 - C.S. File 62/9-8</p> <p>-----</p> <p>Found - In 1960, Byron found evidence of the NE corner of DLC 46 and set a witness corner 88.0 ft. West. WE FIND Byron's cap out of ground and leaning against a bearing tree. Monument is 1" x 36" I.Pipe with brass. We determine position of Witness Corner from found bearing trees: cont.</p> |

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NE Cor. Gillham DLC #46

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

34" now 36" W.Oak with well healed double blaze, bears N.69°W., 5.0 ft.
14" Fir now a 17" stump with lower portion of well healed blaze remaining, bears S.5½°W., 34.5 ft.
23" Fir now 26" with well healed double blaze bears S.17½°E., 57.2 ft. (Rec. S.18½°E.)

From temporary position of Wit. Cor., we then measure East 88 ft. & set a temporary point for the approx. corner position. From this position, we find a 48" dia. B.Oak with a previously opened blaze with a rotted face. As the land owner does not want to have the trees in this area defaced, we do not open for scribing. As this tree fits well for bearing & distance from our temp. corner position, we accept it as the 1892 Briggs BT which Byron found and used. By intersecting distances, we are able to determine a position for the NE corner of DLC #46, from which:

The 48" B.Oak, bears S.34°W., 132.0 ft. (Rec. S.35°W.)

The temporary point set for witness corner, bears S.89°W. 88.0 ft. (Record West)

Set - As the position of the witness corner will fall in a dam & reservoir area and the position of the NE Cor. DLC #46 falls in an area to be landscaped, we set no permanent monument at the witness corner of the DLC corner.

To perpetuate the corner, we reference the NE cor. with 3 positions on a house foundation as noted below in sketch. (See C.S. File 62/9-8) The local magnetic attraction of structure prohibits use of bearings to new accessories in this report.

Fd. R.P.'s Oct. 1999, by D. Edwards - 1999-0086