

PRIMARY CORNER DESCRIPTION SW Cor. Atterbury DLC #47

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - J.A. Burnett, Contract #75, Nov. 22, 1856

Set a post as per instructions, from which
A W.Oak 18" dia., bears N.65°W., 172 lks.

BLM survey by Peterson, Berry, etal, under Group #'s 744 and 838 - Survey May, 1971/Aug. 1974 (DCSO records, Volume 37 Page 15193)

The SW Cor. DLC #47, determined at record courses and distances from the ¼ sec. cor. of secs. 33 & 34; there is no remaining evidence of the original corner. Diligent search was made for all corners around the claim, none of which were recovered.

Set an Iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T 26 S R 7 W
S 33 C
47
1974

from which
A W.Oak 10" dia., bears N.84¼°W., 16 lks. mkd. T26S R7W S33 BT.

No other suitable trees available within limits.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Page(s) 22474-5)

The SW. cor. of DLC No. 47, monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford

A sawed oak stump, 24" dia., bears N.84¼°W., 10.6 ft. with a healed blaze.

and new accessories

An iron rod, 30" long, 5/8" dia., driven 28" in the ground for a reference monument bears N.89°25'17"W. 7.4 ft., with aluminum cap mkd. RM T26S R7W S33 7.4 FT TO COR 2006, & an arrow pointing to the corner.

An iron rod, 30" long, 5/8" dia., driven 28" in the ground for a reference monument bears N.10°27'46"W. 7.0 ft., with aluminum cap mkd. RM T26S R7W S33 7.0 FT TO COR 2006, & an arrow pointing to the corner.