

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36 of T26-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April, 1855 (DCSO records, Volume 11 Page 4591)

Set post, cor. secs. 30, 31, 25, 36, from which

- A Fir 15" dia., bears N.64°E., 15 lks. dist.
- A Fir 12" dia., bears N.44°W., 32 lks. dist.
- A Fir 12" dia., bears S.22°W., 21 lks. dist.
- A Chinquapin 12" dia., bears S.30°E., 37 lks. dist.

GLO survey by S.C. Flint, under Contract #392 dated May, 1881 (DCSO records, Volume 11 Page 4620)

Made and set Laurel post, 40" long, 4" sq., from which
(All trees as described by Hathorn)

Trees and Post found in good condition by W.P. Heydon, GLO survey in 1896. Contract #656. (DCSO records, Vol. 11 Pg.4650)

Bureau of Land Management resurvey by Zirpel and Martin, under Group #'s 350 and 357. Survey April/May 1959 - (DCSO records, Volume 29 Page 12535)

Corner of secs. 25, 30, 31 and 36, perpetuated with a fir post, 4x4 ins. 18" high, firmly set in a mound of stone, 3 ft. base, 1 ft. high, at record bearing and distance from the remains of the original bearing trees:

- The stump hole & roots of a Fir, bears N.64°E., 15 lks.
- A clump of Chinquapin sprouts, bears S.30°E., 37 lks.
- A rotted & burned Fir stump bears S.22°W., 21 lks. dist.
- The stump hole of a Fir bears N.44°W., 32 lks. dist.

and locally established bearing trees:

- A Fir 23" dia., bears N.19°E., 48 lks. dist. with scribe marks 26 visible on a partially healed blaze.
- A Fir 20" dia., bears N.43°W., 48 lks. dist., with scribe marks BT visible on a partially healed blaze.

At the corner point, Set an Iron post, 28" long, 2½" dia., 18" in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T26S
R8W | R7W
S 25 | S 30
S 36 | S 31
1959

(Cont. Next Page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30, 31; 25 & 36 of T26-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

from which new bearing trees
A Fir 18" dia., bears N.14°E., 40 lks. dist. mkd. T26S
R7W S30 BT.
A Fir 6" dia., bears S.16°E., 215 lks. dist. marked
T26S R7W S31 BT.
A Fir 8" dia., bears S.11°W., 197 lks. dist., marked
T26S R8W S36 BT.
A Fir 26" dia., bears N.83°W., 20 lks. dist., marked
T26S R8W S25 BT.
Reset the Fir post alongside the Iron post.

Bruce Shaner Engineering - For: Hub Lumber & Weyerhaeuser Co.
Dec. 21, 1973 - M 49-49

Found - 1959 BLM Cadastral brass cap.
18" D.Fir snag BT, scribing visible, bears N.14°E.,
26.4 ft.
10" D.Fir BT, face visible bears S.16°E., 141.9 ft.
12" D.Fir face visible bears S.11°W., 130.0 ft.
26" D.Fir, windfall, scribing visible, bears
N.83°W., 13.2 ft.
22" D.Fir scribing partially visible, bears
N.43°W., 31.7 ft.
23" D.Fir, snag, windfall, bears N.19°E., 31.7 ft.
New BT - 12" Hemlock scribed "T26S R8W S25 BT" bears
N.45°W., 105.4 ft.

BLM resurvey by Peterson, etal, May 1971/Aug. 1974, found
1959 brass cap and nine BTs. (DCSO rec. Vol. 37 Pgs 15184-85)

Tony Hostetter - March 2011 - C.S. File 65/72-25

Found - 1959 BLM BC, from which
18" Fir snag, 1959 BT, scribing visible, New WEYCO
tag, bears N.14°E., 27.0 ft. (Rec. 26.4')
22" Fir stump, 1959 BT, face evident, BLM tag,
bears; S.16°E., 141.9 ft.
23" Fir stump, (7' tall) face evident, New WEYCO
tag, bears; N.43°W., 31.7 ft.
27" leaning fir, face evident, new WEYCO tag, bears
N.1°W., 23.6 ft.