

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 30; & 24 & 25 of T26-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, under Contract #57 dated April, 1855 (DCSO records, Volume 11 Page 4591)

-----  
Set post, cor. secs. 19, 30, 24 and 25, from which  
A Fir 12" dia., bears N.10°E., 111 lks. dist.  
A Fir 24" dia., bears N.18°W., 142 lks. dist.  
A burnt Cedar 40" dia., bears S.8°W., 133 lks. dist.  
An Alder 4" dia., bears S.64°E., 84 lks. dist.

-----  
GLO survey by S.C. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 11 Page 4620)

-----  
Made and set firmly in the ground, a Fir post, 40" long, 4" square, from which  
(BTs as described by Hathorn)

-----  
Bureau of Land Management resurvey by Zirpel & Martin under Group #'s 350 and 357. Survey April/May 1959 (DCSO records, Volume 29 Pages 12534-35)

-----  
Point for the section corner, is determined at proportionate distance; there is no remaining evidence of the orig. corner. Set an Iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T26S  
R8W|R7W  
S 24|S 19  
S 25|S 30  
1959

Raise a mound of stone, 3½ ft. base, 2 ft. high, west of the corner. No suitable bearing trees are available.

-----  
Bureau of Land Management resurvey by Peterson; Berry; etal, under Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO record, Volume 37 Page 15189)

-----  
The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, in a mound of stone, 3½ ft. base, to top, with 1959 marked brass cap.

From which  
(Cont. Next Page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. 19 & 30; 24 & 25 of T26-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A Fir 7" dia., bears N.15°E., 18 lks. dist.,  
mkd. T26S R7W S19 BT.  
A Fir 8" dia., bears S.18°W., 30½ lks. dist., mkd.  
T26S R8W S25 BT.  
A Fir 6" dia., bears N.6½°W., 40½ lks. dist., mkd.  
T26S R8W S24 BT.  
No other suitable trees available within limits.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21024-5)

-----  
The cor. of secs. 19, 24, 25, & 30, on the W. bdy. of the township, monumented with an iron post, 2½ " dia., firmly set, projecting 5" above ground, with brass cap (properly mkd.  
A mound of stone 3½ ft. base, 2.0 ft. high, is to the West.  
from which the remains of BTs mkd. by Peterson, Berry, Popken, & Wofford  
A stump hole, bears N.15°E., 11.9 ft., with decayed fir alongside, 9 " dia., with a healed blaze.  
A fir, 13 " dia., bears S.18°W., 20.1 ft., with a healed blaze.  
A fir, 11 " dia., bears N.2¼°W., 26.3 ft., with a healed blaze. (Record N.6½°W., 26.7 ft.)  
and new bearing trees  
A fir, 17 " dia., bears N.68½°E., 30.5 ft., mkd. T26S R7W S19 BT.  
A fir, 18 " dia., bears S.72°E., 3.4 ft., mkd. T26S R7W S30 BT.  
Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description