

PRIMARY CORNER DESCRIPTION WC Sec. Cor. 7 & 18; 12 & 13 of T.26-8

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Pages 4589-90)

-----

Marked a Fir, 15" dia., for cor secs 7, 18, 12 & 3, from which

- A Fir 12" dia., bears N.10°W., 32 lks dist.
- A Fir 8" dia., bears N.15°E., 21 lks. dist.
- A Fir 24" dia., bears S.8°W., 160 lks. dist.
- A Laurel 10" dia., bears S.50°E., 20 lks. dist.

GLO survey by S.C. Flint, Contract #392, 1881, found Corner tree & all witness trees. (DCSO record, Vol. 11 Pgs. 4618-19)

Bureau of Land Management survey by Peterson & Berry, under Group #739. Survey May/July 1971 (DCSO recs, Vol 37 Pg 15200)

-----

True point for the cor. of secs. 7, 12, 13 and 18, falls on rock outcropping, 40 ft. high, slopes E.; determined by the method of irregular boundaries; there is not remaining evidence of the original corner.

(.50 chs. N.0°07'W., point selected for the witness corner of secs. 7, 12, 13 and 18)

Set a brass tablet, 3" dia., 3½" stem, in a drill hole in solid rock, mkd.

```

T 26 S
R 8 W R 7 W
S 12 | S 7
S 13 | S 18
      |
      v
      W C
      1971

```

from which

A Madrone 5" dia., bears N.84½°E., 68 lks mkd. X BT.

A Madrone, 4" dia., bears S.61½°W., 90 lks. mkd. X BT.

A Fir 20" dia., bears N.44°W., 125 lks. mkd. X BT.

No other trees available within limits.

The witness corner is located at top of ascent, slopes S.60°E.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21037-8)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22077)

-----

The WC for the cor. of secs. 7, 12, 13, & 8, monumented with a brass tablet, 3" dia., cemented firmly into solid bedrock, (properly) mkd. continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 100501

PRIMARY CORNER DESCRIPTION WC Sec. Cor. 7 & 18; 12 & 13 of T. 26-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which bearing trees mkd. by Peterson and Berry

A madrone, 11" dia., bears N.73½°E., 36.4 ft., with a healed double blaze.

A madrone, 8" dia., bears S.59°W., 41.5 ft., with fragmentary scribe marks visible on partially healed blaze.

A fir, 28" dia., bears N.45¼°W., 63.8 ft., with a healed blaze.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 7/2019 - C.S.  
File 65/102-71

-----  
Found - BLM brass cap (properly mkd)  
11" madrone N.73½°E., 36.4 ft. good scar.  
9" madrone S.59°W., 41.5 ft. good scar.  
30" fir N.45¼°W., 63.8 ft. good scar.  
New - 4" W.Fir N.43°E., 17.8 ft. scribed WC BT  
Note - Compass decl. 15½°E.