

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 1 of T26-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Dennis Hathorn, under Contract #57 dated April 12 1855 (DCSO records, Volume 11 Page 4589)  
-----  
Set ¼ sec. post, from which  
    A Hemlock 12" dia., bears N.45°W., 14 lks. dist.  
    A Hemlock 20" dia., bears N.85°E., 14 lks. dist.

---

GLO survey by S.C. Flint, under Contract #392 dated May 26 1881 (DCSO records, Volume 11 Page 4618)  
-----  
Quarter post, decayed and down. Witness trees found. Made post, 3 ft. long, 3" sq., and set, from which  
    A Hemlock 12" dia., bears N.45°W., 14 lks. dist.  
    A Hemlock 20" dia., bears N.85°W., 14 lks. dist.

---

BLM resurvey by Peterson & Berry, under Group #739, Survey May/July 1971 (DCSO records, Volume 37 Page 15203)  
-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an Iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.  
    1/4  
    S 1|S 6  
    T 26 S  
    R 8 W R 7 W  
    1971  
  
from which  
    A Fir 15" dia., bears N.33°E., 27 lks. dist. mkd. ¼ S6 BT  
    A Fir 20" dia., bears S.42°E., 26 lks. dist. mkd. ¼ S6 BT  
No other suitable trees available within limits.

---

BLM resurvey by Wayne Rogers, under Group #1382, Survey May/August 1987 (DCSO records, Volume 48 Page 18446)  
-----  
The ¼ sec. cor., mounumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with 1971 brass cap. from which the remains of BTs mkd. by Peterson & Berry:  
    A sawed fir stump 15" dia., bears N.43°E., 27 lks. dist., with healed blaze. (Rec. N.33°E.)  
    A Fir 22" dia., bears S.42°E., 26 lks. dist., with healed blaze.  
and a new bearing tree  
    A Fir 29" dia., bears N.69°W., 106 lks. dist. mkd ¼ S1 BT

---

Fd. Ok 8/90 - M 110-55  
Found OK by K. Hoffine, Aug. 2003 - M143-4