

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; Sec. 6 of T27-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 11 Page 4595)

-----  
Set ¼ sec. post, from which  
    A Fir 40" dia., bears N.70°E., 39 lks. dist.  
    A Fir 40" dia., bears S.30°E., 41 lks. dist.

GLO survey by S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Vol. 11 Page 4623)

-----  
Quarter post not found. Witness found. Made and set new Hemlock post, usual size and length, from which,  
    A Fir 40" dia., bears N.70°E., 39 lks. dist.  
    A Fir 40" dia., bears S.31°E., 41 lks. dist.

Doug. County Surveyors Office - Vernon Tracy; March 17, 1966  
C.S. File 54/23-1

-----  
CORNER REPORT ONLY  
Found ½" Iron pipe & Weyerhaeuser BTs "W" nail method as follows:  
    58" D.Fir N.60°E., 36.0 ft. "W" nail under tag.  
    49" D.Fir S.77°E., 36.5 ft. "W" nail under tag.  
We find no original scribe on either BT or record of this visit by Weyerhaeuser. (*Letter in CS file from Weyerhaeuser indicates this might be a corner by John Ohman in 1952 but they did not have any of his notes*) VL

BLM resurvey by Peterson; Berry; Popken and Wofford under Group #s 744 and 838 dated May 1971 and May 1974 (DCSO records Volume 37 Pages 15160-61)

-----  
Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 26 S R 7 W

1/4  $\frac{S\ 31}{S\ 6}$

T 27 S

1974

from which  
    A White Fir 11" dia., bears N.37°W., 243 lks. mkd. 1/4 S31 BT.  
    A sawed Fir stump 28" dia., bears S.64°E., 124 lks. mkd. 1/4 S6 BT.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31; Sec. 6 of T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, an unrecorded iron pipe, ½" dia., firmly set, projecting 8" above ground, bears N.50°20'W., 0.05 chs. dist., from which locally established BTs:  
A sawed fir stump 58" dia., bears N.60°E., 55 lks., with galvanized nail with "W" embossed on head, driven into base.  
A sawed fir stump 49" dia., bears S.77°E., 55½ lks. with galvanized nail with "W" embossed on head, driven into base.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 1999 - M 134-63  
-----

Found - 3" brass cap set by BLM in 1974, from which ½" conduit from unrecorded survey (1951 Haines survey in Weyerhaeuser Company Land use files per narrative) bears N.22°E., 2.2 ft.  
40" Fir stump, WEYCO tag, bears N.56°E., 37.2 ft.  
48" Fir stump, WEYCO tag, bears S.80°E., 37.6 ft.  
New BTS - 10" Fir scribed "S31 ¼ BT" bears N.64°54'E., 13.0 ft. to spike.  
12" Fir scribed "S6 ¼ BT" bears S.65°19'E., 10.7 ft. to spike.  
10" Fir scribed "S6 ¼ BT" bears S.19°05'W., 7.4 ft. to spike.  
10" Fir scribed "S31 ¼ BT" bears N.73°40'W., 4.6 ft. to spike.