

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4631)

Set Laurel post for ¼ sec. cor., 3 ft. long and 3" sq.,
from which
 A chinquapin, 10" dia., bears S.80°W., 12 lks. dist.
 A Fir 10" dia., bears N.10°E., 16 lks dist.

Bureau of Land management resurvey by Peterson, Berry, etal,
under Group #'s 744 and 838. Survey May 1971/Aug. 1974
(DCSO records, Volume 37 Page 15184)

Point for the 1/4 cor., at proportionate distance; there is no
remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 22" in the ground, with
 brass cap mkd. T 26 S R 7 W
 1/4 S 30
 S 31
 1974

from which
 A Cedar 30" dia., bears S.20¾°W., 150 lks. dist., mkd.
 1/4 S31 BT.
 No other suitable tree available within limits.
Corner is located on top of spur, slopes N.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 1999 - M 134-63

Found - 3" brass cap set by BLM in 1974, from which
 12" Fir stump, WEYCO tag, : bears N.0°3'E., 11.3 ft.
 38" Cedar, face evident, BLM tag, bears S.19°41'W.,
 99.0 ft.
 32" Fir, possible face, WEYCO tag, bears S.39°48'W.,
 21.8 ft.
 ½" conduit from unrecorded survey (1951 Haines
 survey in Weyerhaeuser Company Land use files
 per narrative) bears S.66°50'W., 16.21 ft.
New BT - 12" Fir, scribed "S 30 ¼ BT" bears N.57°45'W., 7.1
 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2306, Surveyed April 2010 - (DCSO
records Vol. 57 Page(s) 22763-4 & Survey plat 2012-1 A&B)

The ¼ sec. cor. of secs. 30 and 31, perpetuated by Hostetter.
in 2000. monumented with on iron post, 2½" dia., firmly set,
projecting 2" above ground, with a brass cap (projecting) mkd.
 continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of a BTs mkd. by Peterson, Berry, Popken, and Wofford
A sawed cedar stump, 38" dia., bears S.19¼°W., 99.0 ft., with no marks visible. (Record, S.20¾°W.)
and the remains of BTs mkd. by person(s) unknown, reported by Hostetter
A decayed fir stump, size indeterminate, bears N.0¼°E., 11.1 ft., with no marks visible.
A sawed fir stump, 23" dia., bears S.39¾°W., 22.0 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Hostetter
A sawed fir stump, 13" dia., 5 ft. high, bears N.53¼°W., 8.0 ft., with illegible scribe marks visible on a partially healed blaze.
and new accessories
A rebar, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears N.14°26'02"E., 22.96 ft. with aluminum cap mkd. RM T26S R7W 1/4 S30 23.0 FT TO COR 2010 and an arrow pointing to the corner.
A fir, 11" dia., bears S.70¼°E., 25.9 ft.. mkd. ¼ S31 BT.
From this corner, a point established by Wilford N. Haines. in 1951, in on unfiled survey for Weyerhaeuser Timber Company, reported by Hostetter, bears S.67°55' 53" W., 16.18 ft., monumented with a stainless steel pipe, 3/4" dia., firmly set, bent N., projecting 8" above ground, and is not utilized during the course of this survey.
(NAD 1983 (CORS))
Latitude 43°16'20.18" N. Longitude 123°34'29.34"W