

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Pages 4633-34)

Set Cedar post, 3 ft. long and 4" sq., firmly in the ground,
from which

A Laurel 6" dia., bears N.65°W., 16 lks. dist.

A Laurel 7" dia., bears S.55°E., 10 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal,
under Group #'s 744 and 838. Survey May 1971/Aug. 1974
(DCSO records, Volume 37 Page 15188)

Point for the 1/4 cor., at proportionate distance; there is no
remaining evidence of the original corner.

Set an Iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd.

T 26 S R 7 W

1/4 $\frac{S\ 19}{S\ 30}$

1974

from which

A Fir 6" dia., bears N.44°E., 29½ lks. mkd. 1/4 S19 BT.

A Fir 8" dia., bears S.67°W., 36½ lks. mkd. 1/4 S30 BT.

FD. Ok, BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21023-4)