

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 18 and 19

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Original - S. C. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 11 Page 4635)

Set a Cedar post, 3 ft. long, 3" sq., from which
A Fir 40" dia., bears N.25°W., 13 lks. dist.
A Fir 6" dia., bears S.30°E., 13 lks. dist.

Bureau of Land Management resurvey by Roseberry, under Group #696. Survey July 1969 (DCSO records, Vol. 36 Pg. 14864)

Point for the ¼ cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 24" in the ground, with brass cap mkd.

T 26 S R 7 W

1/4 $\frac{S\ 18}{S\ 19}$

1969

from which

A Fir 6" dia., bears N.16½°W., 11½ lks., mkd. ¼ S18 BT.

A Fir 5" dia., bears S.23½°E., 20½ lks., mkd. ¼ S19 BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Page(s) 22472-3)

The ¼ sec. cor. of secs. 18 and 19, monumented with an iron post, 2½" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Roseberry

A fir, 14" dia., bears S.15°E., 13.5 ft., with a healed blaze. (Record, S.23½°E.)

A fir, 16" dia., bears N.16½°W., 7.6 ft., with a healed blaze.