

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Pg 22477)

-----  
Point for the center ¼ sec. cor. of sec. 18, at intersection with the E. and W. centerline of sec. 18.  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T26S R7W

C ¼  
S 18  
2006

from which

A fir, 17" dia., bears N.19¾°E., 33.5 ft., mkd. C ¼ S18 BT

A fir, 9" dia., bears S.22¾°W., 41.1 ft., mkd. C ¼ S18 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ken Hoffine - For: Lone Rock Timberland Co. - April 2017 - C.S. File 65/96-9

-----  
Found - 2006 BLM brass cap per DCSO records Vol. 57 PG. 22477

23" Fir bears N.20½°E., 33.4 ft. (Record N.19¾°E., 33.5 ft.) Healed face and tag

12" Fir bears S.22°W., 41.1 ft. (Record S.22¾°W., 41.1 ft.) Healed face and tag

New - 7" D.Fir bears N.82¼°E., 22.6 ft. We scribe ¼ S18 BT

16" D.Fir bears S.73¼°W., 34.5 ft. We scribe T26S R7W ¼ S18 BT and tag

Corner lies on West facing slope approx. 100 ft. South and East of draw.