

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4637)

Set a Fir post 3 ft. long & 4" sq., from which
A Fir 36" dia., bears S.25°W., 31 lks. dist.
A Hemlock 6" dia., bears N.15°W., 30 lks. dist.

Ronald Geisler, L.S. #1988 - for: Champion International
Sept/Dec. 1983 - M 90-51

Set - 2½" alum. cap set on a 1" x 36" Iron pipe.
New BTs - 9" Fir bears N.53°W., 10.4 ft. scribed 1/4 S7 BT.
34" Fir bears S.31°W., 15.3 ft. scribed ¼ S18 BT.
A 3/4" Iron pipe set by BLM in 1979, bears N.59°W., 5.91 ft.
from the cap.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert H. Browning, Surveying Tech. under Group
#2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22088)

The ¼ sec. cor. of secs. 7 & 18, established by Geisler, in
1983, and is accepted as the corner, monumented with an iron
pipe, 2½" dia., firmly set, projecting 2" above the ground,
with brass cap (properly) mkd.

from which bearing trees mkd. by Geisler
A fir, 43" dia., bears S.31¼°W., 15.5 ft., with a healed
blaze.
A fir, 12" dia., bears N.55¾°W., 10.0 ft., with a healed
blaze.

From this corner, a point established by the BLM, in 1979,
during the course of an unofficial Administrative Survey,
recorded in the Douglas County Surveyors Office, Map File No.
M80-80, and is not utilized during the course of this survey,
bears N.64°30'58"W., 5.94 ft., monumented with an iron pipe,
¾" dia., firmly set, projecting 1" above the ground, there is
no longer any evidence of the bearing trees referenced to.
Leave the iron pipe in place, as was tied to and referenced
on the plat filed by Geisler.

FD. & Used on BLM Dependent resurvey by Timothy J. Moore,
Cadastral Surveyor and Robert H. Browning, Survey Tech, under
Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57
Page(s) 22477)

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ken Hoffine - For: Lone Rock Timberland Co. - April 2017 -
C.S. File 65/96-9

Found - Alum. Cap set by Geisler in M90-51
47" Fir bears S.31 $\frac{3}{4}$ °W., 15.0 ft. (Record S.31 $\frac{1}{4}$ °W.,
15.5 ft.) healed face and tag
13" Fir bears N.54 $\frac{3}{4}$ °W., 10.1 ft. (Record N.55 $\frac{3}{4}$ °W.,
10.0 ft.) Healed face and tag
BLM ADMIN. 3/4" iron pipe bear N.64°42'26"W., 5.93
ft. (Record N.64°30'58"W., 5.94 ft.)
New - 20" D.Fir bears N.83 $\frac{1}{2}$ °E., 26.4 ft. We scribe T26S
R7W $\frac{1}{4}$ S7 BT and tag tree
Corner lies on NW slope approx. 125 ft. North of dirt road.
Aluminum "L" post on north side of cap.