

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - S.C. Flint, under Contract #392 dated May, 1881 (DCSO records, Volume 11 Page 4638-39)

Set Fir post for ¼ cor., 3 ft. long, 3" sq., from which
A Laurel 12" dia., bears S.30°E., 25 lks. dist.
A Laurel 14" dia., bears N.15°W., 55 lks. dist.

Bureau of Land management resurvey by Peterson; Berry; etal, under Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO records, Volume 37 Page 15191)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, supported by a mound of stone, 3 ft. base, to top, with brass cap mkd.

1/4 $\frac{S\ 6}{S\ 7}$
T 26 S R 7 W
1971

from which
A Fir 22" dia., bears N.19°W., 40 lks. mkd. ¼ S6 BT.
A Fir 20" dia., bears S.45°E., 93 lks. mkd. ¼ S7 BT.

Found OK by K. Hoffine, Aug. 2003 - M143-4

BLM Dependent resurvey by Timothy Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg(s) 22093-4)

The ¼ sec. cor. of secs. 6 & 7, monumented with an iron post, 2½" dia., firmly set, projecting 18 ins. above the ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Peterson, Berry, Popken, and Wofford

A sawed and decayed fir stump, 25" dia., bears S.45°E., 61.4 ft., with scribe marks ¼ S6 BT visible on open blaze.

A sawed and decayed fir stump, 25" dia., bears N.19°W., 26.4 ft., with a healed blaze.

and new bearing trees

A fir, 9" dia., bears N.75¼°E., 27.1 ft., mkd.¼ S6 BT.

A fir, 6" dia., bears S.9¾°W., 12.3 ft., mkd.¼ S7 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Corner is located south, 2.5 ft., of a rock face, 6 ft. high, edge bears N.80°W. and S.80°E.