

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 31 of T25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 1855 (DCSO records, Volume 9 Pages 3857-58)

Set ¼ sec. post, from which
A Fir 8" dia., bears N.65°W., 8 lks.
A Cedar 36" dia., bears S.45°W., 9 lks.

GLO survey by A.R. and S.C. Flint, under Contract #392 dated May, 1881 (DCSO records, Volume 9 Page 3901)

Found old post, decayed and down, also found witness trees, made and set a Fir post, 3 ft. long, 4" sq., from which
A Fir 8" dia., bears N.65°W., 8 lks. dist.
A Cedar 36" dia., bears S.45°W., 9 lks. dist.

Bureau of Land management resurvey by Peterson; Berry; etal; under Group #'s 744 & 838. Survey May 1971/Aug. 1974. (DCSO records, Volume 37 Page 15163)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an Iron post, 28" long 2½" dia., 24" in the ground, with brass cap mkd: T 25 S R 7 W
1/4 $\frac{S \ 31}{S \ 6}$
T 26 S
1971

from which
A Fir 10" dia., bears N.41°W., 35 lks. dist., mkd. ¼ S31 BT.
A Fir 15" dia., bears S.30°W., 24 lks. dist., mkd. ¼ S6 BT.

Burton W. Holt, L.S. #418. For: Sun Studs - May 13, 1985
C.S. File 63/8-12

Found - 1971 BLM brass cap.
20" Fir bears S.30°W., 16.2 ft.
This area was to be logged in 1984 so I removed the pipe and cap and replaced with a 5/8" x 30" iron rod set deep in the ground in the exact position of the pipe and BC. After the logging and slash burning, I RESET the pipe and BC in its
(Cont. Next Page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6; & 31 of T25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

original position putting it directly over the iron rod.
New Accessory:

The orig. BT is now a 20" Fir stump 7 ft. tall. I
rescribed the tree "1/4 S BT" and nailed a
bearing tree tag on west side facing road.
Corner is on a landing 50 ft. East of road. No other tree
available.

Kristian DeGroot - surveyed for Jerry Lamb, June 1994 M119-33

Found - 2" iron pipe with a 3/4" USBLM brass cap by Popken in
1975, firmly set projecting 6" above ground,
properly marked from which:
18" high stumped D.Fir bears S.30°W., 16.2 ft. with
scribe marks "1/4 S6 BT" visible.

New BTs -
11" W.Fir bears S.75°W., 80.3 ft. scribed "1/4 S6 BT"
18" D.Fir bears S.2°W., 118.6 ft. scribed "1/4 S6 BT"

Found OK by K. Hoffine, Aug. 2003 - M143-4