

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint, under Contract #392 dated May, 1881
(DCSO records, Vol. 11 Page 4630)

I set a Cedar post, 40" long, 4" sq., from which
A Fir 10" dia., bears N.10°E., 6 lks. dist.
A Fir 10" dia., bears S.30°E., 55 lks. dist.
A Fir 20" dia., bears S.60°W., 50 lks. dist.
A Fir 15" dia., bears N.50°W., 62 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal,
under Group #'s 744 and 838. Survey May 1971/Aut. 1974 (DCSO
records, Volume 37 Page 15182)

Point for corner, at proportionate distance; there is no
remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 22" in the ground, with
brass cap mkd.

T 26 S R 7 W

S 30 | S 29

S 31 | S 32

1974

from which

A Fir 6" dia. bears N.41°E., 31 lks. mkd. T26S R7W S29 BT

A Madrone 7" dia., bears S.30°E., 75 lks. mkd. T26S R7W
S32 BT.

A madrone 6" dia., bears S.53½°W., 38 lks. mkd. T26S R7W
S31 BT.

A Fir 32" dia. bears N.36°W. 73 lks. mkd. T26S R7W S30 BT

Corner is located on top of spur, slopes N.50°W.

Found OK, by T.Hostetter, Nov. 1999 - M134-63 Hostetter also
reports a ½" conduit from an unrecorded survey that
bears S.40°49'W., 34.52 ft.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21019-20)

The cor. of secs. 29, 30, 31, & 32, monumented with an iron
post, firmly set, projecting 6" above ground, with brass cap
(properly) mkd. from which BTs mkd. by Peterson, Berry,
Popken, & Wofford

A fir, 11" dia. bears N.41°E., 20.5 ft. with healed blaze
A madrone, 11" dia., bears S.30°E., 49.5 ft., with a
healed blaze.

A madrone, 6" dia., bears S.53½°W., 25.1 ft., with scribe
marks 26S R7W S31 BT visible on partially healed
blaze.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 32" dia. bears N.36°W. 48.2 ft. with a healed blaze
From this point a point established by Wilford N. Haines, in
1951, according to the narrative on the survey plat by Tony
Hostetter, in 1999, monumented with an aluminum conduit pipe,
½" dia., firmly set, projecting 15" above ground, bears
S.40°41'23"W., 34.56 ft., and is not utilized during the
course of the Hostetter survey or this survey.