

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4632)

I set a Laurel post, 3 ft. long and 4" sq., from which
A Fir 30" dia., bears S.30°E., 36 lks. dist.
A Fir 8" dia., bears N.20°E., 41 lks. dist.
A Fir 6" dia., bears N.60°W., 55 lks. dist.
A Fir 6" dia., bears S.20°W., 29 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal,
under Group #'s 744 and 838. Survey May 1971/Aug. 1974 (DCSO
records, Volume 37 Pages 15186-87)

Point for the corner, at proportionate distance; there is no
remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd:

T 26 S R 7 W

S 19 | S 20

S 39 | S 29

1974

from which

A Fir 6" dia. bears N.63½°E. 45 lks. mkd. T26S R7W S20 BT
A Fir 6" dia. bears S.21°E., 35 lks. mkd. T26S R7W S29 BT
A Fir 6" dia. bears S.53°W., 16 lks. mkd. T26S R7W S30 BT
A Fir 6" dia. bears N.35½°W. 15 lks. mkd. T26S R7W S19 BT

FD. Ok, BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21021-2)

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68