

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4634)

I set a Hemlock post, 40" long, 4" sq., from which
A Fir 10" dia., bears S.45°W., 7 lks. dist.
A Fir 8" dia., bears N.35°W., 7 lks. dist.
A Fir 10" dia., bears S.50°E., 26 lks. dist.
A Fir 10" dia., bears N.45°E., 16 lks. dist.

Bureau of Land Management resurvey by Roseberry, under Group
696. Survey July 1969 (DCSO records, Volume 36 Pg. 14862)

Point for the sec. cor., at proportionate distance; there is
no remaining evidence of the original corner.

Set an Iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd.

T 26 S R 7 W

S 18 | S 17

S 19 | S 20

1969

from which

A Fir 5" dia. bears N.17¾°E. 71 lks. mkd. T26S R7W S17 BT

A Fir 5" dia., bears S.16°E. 28 lks. mkd. T26S R7W S20 BT

A Fir 5" dia. bears S.72½°W. 39½ lks. mkd. T26S R7W S19BT

A Fir 5" dia. bears N.52°W., 37 lks. mkd. T26S R7W S18 BT

FD. Ok, BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21026)

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68