

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - S. C. Flint, under Contract #392 dated May 1881  
(DCSO records, Volume 11 Pages 4635-36)

-----  
Set a Fir post, 3 ft. long, 4" sq., from which  
A Laurel 12" dia., bears S.55°E., 31 lks. dist.  
A Laurel 6" dia., bears S.35°W., 11 lks. dist.

Bureau of Land Management resurvey by Roseberry under Group  
# 696 . Survey July 1969 (DCSO records, Vol. 36 Pg. 14865)

-----  
Point for the ¼ sec. cor., at proportionate distance; there  
is no remaining evidence of the original corner.  
Set an Iron post 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd. T 26 S R 7 W  
1/4  
S 18 | S 17  
1969

from which  
A Madrone 6" dia., bears S.47¼°E., 17 lks. mkd. ¼ S17 BT  
A Fir 47" dia., bears S.35½°W., 63 lks., mkd. ¼ S18 BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral  
Surveyor and Robert H. Browning, Survey Tech, under Group No.  
2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Page(s)  
22473-4)

-----  
The ¼ cor. of secs. 17 & 18, monumented with an iron post,  
2½" dia., firmly set, projecting 6" above the ground, with  
brass cap (properly) mkd.  
from which the remains of bearing trees mkd. by Roseberry  
A madrone snag, 7" dia., bears S.47¼°E., 11.2 ft., with  
a healed blaze.  
A fir, 50" dia., bears S.35½°W., 41.6 ft., with a healed  
blaze.  
and a new bearing tree  
A fir, 8" dia., bears S.69¼°E., 9.5 ft., mkd. ¼ S17 BT.

Ken Hoffine - For: Lone Rock Timberland Co. - April 2017 -  
C.S. File 65/96-9

-----  
Found - 1969 BLM brass cap per DCSO Vol. 36 PG. 14865  
50" Fir bears S.34¾°W., 41.0 ft. (Record S.35½°W.,  
41.6 ft.) Healed face and tag  
11" Fir bears S.69¾°E., 9.5 ft. (Record S.69¼°E.,  
9.5 ft.) Healed face and tag  
New - 11" D.Fir bears N.55°W., 16.2 ft. We scribe T26S  
R7W S18 1/4 BT AND TAG continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" Douglas bears N.17¼°E., 15.8 ft. We scribe T26S  
R7W S17 ¼ BT and tag corner lies on West facing  
slope.