

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - S.C. Flint, Under Contract #392, dated May 1881
(DCSO records Volume 11 Page 4636)

Corner to secs. 7, 8, 17 and 18 to which I set a Laurel
Post, 40" long and 4" sq., from which
A Fir 18" dia., bears N.85°W., 61 lks. dist.
A Fir 20" dia., bears N.85°E., 23 lks. dist.
A Hemlock 8" dia., bears S.75°W., 58 lks. dist.
A Fir 8" dia., bears S.80°E., 98 lks. dist.

Doug. County Surveyors Office - James W. Byron, Deputy -
May 13, 1957 - C.S. File 47/191-1

Found - Orig. NE BT which shows good but faint scribe marks
Same for orig. NW BT. check for bearing. The NW BT
measures 37.5 (Rec. 40.3 ft.) (steep slope to
BT).

Also found base of rotted stump of orig. BT,
S.80°E. 64.7 ft.

Found old stump hole for SW BT.

Original NE and NW BTs now 40" Firs.

Set an Iron pipe with brass cap at cor. mkd. County Surveyor
Sec. Corner 7|8 Office 1957
18|17 T26S R7W

Blazed and scribed:

5" Hemlock S.72°E., 34.6 ft. mkd. S 17 CS BT.

6" W.Fir N.68°W., 29.3 ft. mkd. S7 T26S R7W CS BT.

8" R.Fir S.84°W., 36.5 ft. mkd. S18 T26S R7W CS BT.

Rebark and scribed orig. NE BT, S8 T26S R7W CS BT. (N85°E.,
15.2 ft.)

BLM resurvey found OK, brass cap & 5 BTs. By Lynn Roseberry
under Group #696, 1969 (DCSO records, Vol. 36 Pg. 14866)

Doug. County Surveyors Office - Larry E. Monrean, Deputy -
T.R. Plouff - Sept. 29, 1981 - C.S. File 61/27-58

Not found, Orig. corner monument and brass cap set by Byron.
Found - Orig. 20" Fir now 42" stump bears N.85°E., 15.2 ft.
This tree cut low, no scribing remains.

Orig. 18" Fir now 32" bears N.82½°W., 38.1 ft.
(orig. rec N.85°W., 40.3 ft) Bark scribed: T
R W remains.

Stump hole at record bearing & distance to SE orig.
BT remains.

Face measurement to orig. diameter used for distance to the
original bearing trees. continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" uprooted stump (orig. 5" hemlock) bears S.74½°E., 36.2 ft. (Rec. S.72°E., 34.6 ft.)
10" W.Fir (orig. 5") with well healed double blaze bears N.67°W., 29.3 ft. (rec. N.68°W.)
8" R.Fir now 12" with well healed double blaze bears S.84°W., 36.5 ft.
Set at position from which bearings & distances are noted above, I set a 1" x 30" I.Pipe with attached brass cap stamped: Douglas County Surveyor T26S R7W S7 S8 S18 S17 1981. Monument lies on steep northerly slope. Mound stone around northerly base. Cap protrudes 2" above ground.
New BT - 14" Hemlock double blazed & scribed "T26S R7W S17 CS BT" bears S.81°E., 63.4 ft. to center.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCS0 rec Vol 56 pgs 22087-8)

The cor. of secs. 7, 8, 17, & 18, remonumented by Monrean, in 1981, monumented with an iron pipe, 1" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd. from which the remains of original bearing trees
A sawed fir stump, 37" dia., bears N.85°E., 15.2 ft., with a healed blaze.
A fir, 36" dia., bears N.85°W., 38.2 ft., with fragmentary scribe marks visible on the bark.
and the remains of BTs mkd. by Byron, reported by Roseberry
A fir, 14" dia., bears S.84°W., 36.3 ft., with a healed double blaze.
A fir, 16" dia., bears N.68½°W., 29.0 ft. with a healed double blaze and a bearing tree mkd. by Monrean
A hemlock, 21" dia., bears S.82°E., 62.9 ft., with a healed double blaze.

Ken Hoffine - For: Lone Rock Timberland Co. - April 2017 - C.S. File 65/96-9

Found - 1981 Douglas CO brass cap per DCS0 CS 61/27
37" Fir stump bears N.85°E., 15.2 ft. as per record
36" Fir bears N.85°W., 38.2 ft as per rec healed face & tag
14" Fir bears S.84°W., 36.3 ft. as per rec healed face & tag
16" Fir bears N.68½°W., 29.0 ft. as per rec healed face & tag
21" Hemlock bears S.82°E., 62.9 ft. as per record healed face and tag
Corner lies on steep East facing slope at NE corner of 8 to 10 year old plantation.