

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - S.C. Flint, under contract #392 dated May, 1881 (DCSO records, Volume 11 Page 4637)

-----  
Set Cedar post, 3 ft. long, 3" sq., from which  
A Fir 8" dia., bears S.60°E., 23 lks. dist.  
A Cedar 36" dia., bears S.65°W., 57 lks. dist.

Ronald Geisler, L.S. #1988, For: Champion International Corp. Sept/Dec. 1983 - M 90-51

-----  
Set - 2½" alum. cap set on a 1" x 36" Iron pipe.  
New BTs - 10" Fir bears S.54°W., 24.9 ft. scribed ¼ S8 BT.  
4" Fir bears N.22°W., 27.5 ft. scribed ¼ S7 BT.  
A ¾" Iron pipe extending 31" above ground, set by the BLM in 1968, bears N.4°05'E., 1.21 ft. from the cap.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec Vol 56 pgs 22090-1)

-----  
The ¼ sec. cor. of secs. 7 & 8, reestablished by Geisler, in 1983, and is accepted as the corner, monumented with an iron pipe, 2" dia., firmly set, flush with the ground, with aluminum cap (properly) mkd.

from which bearing trees mkd. by Geisler  
A fir, 23" dia., bears S.55¼°E., 25.0 ft., with a healed double blaze.  
A fir, 13" dia., bears N.25¼°W., 27.4 ft., with a healed double blaze.

From this corner, a point established by the BLM, in 1968, during the course of an unofficial Administrative Survey, and is not utilized during the course of this survey, bears N.15°38'53"E., 1.07 ft., monumented with an iron pipe, ¾" dia., firmly set, projecting 28" above the ground, from which the bearing trees referenced to, and not mkd.

A madrone, 12" dia. bears S.35°E., 14.9 ft no marks visible  
A madrone, 11" dia. bears N.19½°W., 16.3 ft no marks visible  
Leave the iron pipe in place, as was tied to and referenced on the plat filed by Geisler.

The geographic position (NAD 1983 (CORS)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System Stations noted above, is as follows:

Latitude: 43°19'23.54" N. Longitude: 123° 33'51.95" W.