

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 and 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - S. C. Flint, under Contract #392 dated May 1881  
(DCSO records, Volume 11 Page 4639)

-----  
Set Fir post, 3 ft. long, 4" sq., from which  
A Fir 36" dia., bears N.80°W., 2 lks. dist.  
A Fir 20" dia., bears S.75°E., 6 lks. dist.

-----  
Bureau of Land Management resurvey by Peterson; Berry; etal,  
under Group #'s 744 and 838. Survey May 1971/Aug. 1974  
(DCSO records, Volume 37 Page 15192)

-----  
Point for the 1/4 sec. cor, at proportionate distance; there  
is no remaining evidence of the original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the  
ground, with brass cap mkd:

1/4  
S 6|S 5  
T 26 S R 7 W  
1971

from which

A Fir 17" dia., bears N.5°E., 23 lks. dist.,  
mkd. 1/4 S5 BT.

A Fir 42" dia., bears N.39¼°W., 71 lks. dist.,  
mkd. 1/4 S6 BT.

Found OK by K. Hoffine, Aug. 2003 - M143-4