

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 of T. 25-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April, 1855 (DCSO records, Volume 9 Page 3857)

-----  
Set post cor. secs. 5, 6, 31 and 32, from which  
A Fir 36" dia., bears N.78°E., 11 lks.  
A Laurel 6" dia., bears N.73°W. 12 lks.  
A Laurel 10" dia., bears S.35°E., 64 lks.  
A Laurel 10" dia., bears S.62°W., 13 lks.

-----  
GLO survey by A.R. and S.C. Flint, under Contract #392 dated May, 1881 (DCSO records, Volume 9 page 3901)

-----  
Cor. to secs. 5, 6, 31 and 32. Post rotted down. Witness trees all standing. Made new Cedar post, 40" long, 4" sq., set firmly in the ground from which:  
(All BTs. listed by Hathorn)

-----  
Richard C. Grant; D. Powell; W. Oiler - For: Martin Bros. Box Co. Feb. 20, 1958 - C.S. File 42/372-1

-----  
Found - Stump hole on edge of small bluff, Laurel roots, that bears S.35°E., 42 ft.  
Uprooted large Fir that bears N.78°E., 7 ft., burned roots still remain.  
Laurel clump that will fit for proper distance and bearing for other two trees. Did not find any blazes to the West, though a 50 ft. rock bluff fit the called distance.  
Top of ridge to the North fits called distance of 2 chains, also creek at 12.00 chains.  
I Set a 4" x 4" x 48" Cedar post for the corner and scribed the following trees:  
24" Fir that bears N.2½°E., 28.6 ft. S32 T25S R7W.  
6" Madrone bears N.55½°W., 5.8 ft. S31 T25S R7W.  
6" Fir that bears S.49°W., 16.6 ft. S6 T26S  
10" Fir that bears S.30½°E., 11.2 ft. S5 T26S R7W.

-----  
Bureau of Land Management resurvey by Peterson, Berry, etal, under Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO records, Volume 37 Pages 15162-63)

(Cont Next page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 of T25-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Corner, perpetuated and recorded by Richard Grant, in 1958, monumented with the remains of the cedar post, 4" sq., projecting 4" above ground, from which the remains of the original bearing trees:

A root hole bears N.78°E., 11 lks. dist.

A root hole bears S.35°E., 64 lks. dist.

and bearing trees mkd. by Grant:

A Fir 26" dia., bears N.2½°E., 43 lks. dist., with scribe marks S32 T25S R7W BT visible on bark blaze.

A Fir 11" dia., bears S.30°E., 18 lks. dist., with healed blaze.

A Fir 7" dia., bears S.49°W., 26 lks. dist., with healed blaze.

A Madrone 10" dia., bears N.55°W., 9 lks. dist., with scribe marks S31 T25S R7W visible on bark blaze.

At the corner point, Set an Iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 25 S R 7 W

S 31 | S 32  
S 6 | S 5  
1971

from which new bearing trees

A Fir 5" dia., bears N.78°E., 43 lks. dist., mkd. X BT.

A Fir 37" dia., bears N.12°W., 72 lks. dist., mkd.

T25S R7W S31 BT.

Bureau of Land Management resurvey by Peterson & Berry under Group #739. Survey May/July 1971 (DCSO records, Volume 37 Pages 15204-05)

-----  
Corner of secs. 5, 6, 31 and 32, monumented with an iron post, 2½" dia., firmly set, protruding 4" above ground, with brass cap mkd. as in 1971.

from which the remains of the original bearing trees

A root hole bears N.78°E., 11 lks. dist.

A root hole bears S.35°E., 64 lks. dist.

and trees mkd. by Grant in 1958

A Fir 26" dia., bears N.2½°E., 43 lks. dist., with scribe marks S32 T25S R7W BT visible on bark blaze.

A Fir 11" dia., bears S.30°E., 18 lks. dist., with healed blaze.

A Fir 7" dia., bears S.49°W., 26 lks. dist., with healed blaze.

A Madrone 10" dia., bears N.55°W., 9 lks. dist., with scribe marks S31 T25S R7W visible on bark blaze.

and new bearing trees

(Cont. Next page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. 5 & 6; 31 & 32 of T25-7

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 5" dia., bears N.78°E., 43 lks. dist., mkd. X BT.  
A Fir 37" dia., bears N.12°W., 72 lks. dist., mkd. T25S  
R7W S31 BT.