

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 240140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21031)

Point for the center ¼ sec. cor. of sec. 32, at the intersection with the E. and W. centerline.
Set a stainless steel post, 28" long, 2½" dia., 16" in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 26 S R 7 W
C 1/4 S 32
2002

from which

A fir, 20" dia., bears N.25¾°E., 22.4 ft., mkd. C¼ S32 BT.
A fir, 15" dia., bears S.46°W., 8.4 ft., mkd. C¼ S32 BT.
Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description
Deposit a magnet in a white plastic case at the base of the stainless steel post.