

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4630)

Set a Fir post for ¼ sec. cor., 3 ft. long, 3" sq., from
which

A Fir 12" dia., bears N.40°E., 19 lks. dist.

A Fir 12" dia., bears S.55°E., 10 lks. dist.

Bureau of Land Management survey by Peterson, Berry, etal,
under Contract #'s 744 and 838. Survey, May 1971/Aug. 1974
(DCSO records, Volume 37 Page 15183)

Point for the 1/4 sec.cor., at proportionate distance; there
is no remaining evidence of the original corner.

Set an Iron post, 28" long, 2½" dia., 22" in the ground, with
brass cap mkd. T 26 S R 7 W

1/4 $\frac{S\ 29}{S\ 32}$

1974

from which

A W.Fir 14" dia., bears N.76°E., 46 lks. dist.

mkd. 1/4 S29 BT.

A W.Fir 10" dia., bears S.74½°E., 54 lks. dist.

mkd. 1/4 S32 BT.