TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias Description
Alias Description
Alias Description
Alias Description

Original - S. C. Flint, under Contract #392 dated May 1881
(DCSO records, Volume 11 Page 4633)

Set a Laurel post, from which
A Chinquapin 6" dia., bears N.65°W., 15 lks. dist.
A Laurel 7" dia., bears S.50°E., 10 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal, under Group #'s 744 & 838. Survey May 1971/Aug. 1974
(DCSO records, Volume 37 Page 15187)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 26 S R 7 W

1/4 S 20 / S 29

1974

from which
A Fir 6" dia., bears N.42°W., 25½ lks. mkd. 1/4 S20 BT.
A Fir 6" dia., bears S.65°W., 18 lks. mkd. 1/4 S29 BT.

FD. Ok, BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21022)

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68