

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for 5; & 32 of T 25-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Original - Dennis Hathorn, under Contract #57 dated April 1855 (DCSO records, Volume 9 Page 3857)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Fir 24" dia., bears N.24°E., 16 lks. A Fir 20" dia., bears S.12°E., 50 lks.</p>
<p>GLO survey by A.R. and S.C. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 9 Page 3901)</p> <p>-----</p> <p>¼ post and witness trees probably destroyed by fire, made new post, 3 ft. long, 3" sq., and set firmly in the ground, from which A Fir 24" dia., bears N.24°E., 16 lks. dist. A Fir 20" dia., bears S.12°E., 50 lks. dist.</p>
<p>Richard C. Grant; D. Powell; W. Oiler - For: Martin Bros. Box Co. - Feb. 20, 1958 - C.S. File 42/372-2</p> <p>-----</p> <p>Set a Fir post, from which 30" Fir bears S.33°E., 8.0 ft. mkd. ¼ S5 BT. 16" madrone bears N.18½°W., 12.9 ft. mkd. ¼ S32 T25S R7W 2807.</p>
<p>Doug. County Surveyors Office - John M. Powell; Jack Heritage; Gary Commons - Feb. 24, 1973 - C.S. File 56/25</p> <p>-----</p> <p>Found - 30" D.Fir now 35" S.33°E., 8.0 ft. shows good scar. 16" Laurel now 18" N.18½°W., 12.9 ft. bark scribe visible. 2807 - S32 T25S R7W BT. Set - Drove 5/8" Iron rod at ¼ corner. New BT - 9" D.Fir S.27°W., 6.5 ft. scribed ¼ S5 CS BT.</p>
<p>David Edwards - Nov. 4, 1999 - C.S. File 65/23-16</p> <p>-----</p> <p>Found - 5/8" dia., iron rod. 40" Fir stump, S.33°E., 8.0 ft. 22" Madrone N.18½°W., 12.9 ft. (Attached BT Tag) 10" Fir stump S.27°W., 6.5 ft. New B0s- 12" dia., Fir scribed "¼ S5 BT" 6 ft. steel fence post 2 ft. North.</p>
<p>David Edwards - For: Seneca Jones Timber Co. - March 9, 2011 - C.S. File 65/74-3</p> <p>-----</p> <p>Found - 5/8" IR by DCS in 1973 BTs per CS 65/23-16</p>