

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5 of T27-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 11 Page 4594)

Set post, cor. secs. 32, 33, 4 and 5, from which
A Fir 15" dia., bears N.75°E., 18 lks. dist.
A Fir 15" dia., bears N.67°W., 45 lks. dist.
A Fir 24" dia., bears S.23°W., 75 lks. dist.
A Fir 18" dia., bears S.89°E., 90 lks. dist.

GLO survey by S.C. Flint, under contract #392 dated May 26, 1881 (DCSO records, Vol. 11 Pages 4621-22)

Old post gone. Witness trees all found. Made and set new Laurel post 42" long, 3" sq., from which the witness bear as follows:

A Fir 15" dia., bears N.75°E., 18 lks. dist.
A Fir 15" dia., bears N.67°W., 45 lks. dist.
A Fir 24" dia., bears S.23°W., 75 lks. dist.
A Fir 18" dia., bears S.89°E., 90 lks. dist.

N.E. Richardson; B.A. Lane; P.D. Wolford; Otto Mathews May 1934 - (No record source found. See "old" corner book, Page 98)

Set a 2 x 30" Iron pipe from old BTs. They were in good shape. remarked same.

Fir 15" dia., bears N.75°E., 18 lks. dist.
Fir 15" dia., bears N.67°W., 45 lks. dist.
Fir 18" dia., bears S.89°E., 90 lks. dist.
Fir 24" dia., bears S.23°W., 75 lks. dist.

BLM survey by Zirpel and Martin under Group #'s 350 and 357 dated April 1957. Survey in 1959 (DCSO records, Vol. 29 Pages 12538)

Corner bears S.0°17'W., 161.20 chains from Sec. Cor. for 20, 21, 28 and 29 of T.26-7; perpetuated with an Iron pipe 4" above ground, firmly set, at record distance from each of the original bearing trees:

A Fir 36" dia., bears N.75¾°E., 18 lks. dist. with partially opened & burned blaze. (Rec.brg. N.75°E)
(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

and the remains of a bearing tree mkd. by Zirpel and Martin
A sawed fir stump, 28" dia., bears S.68½°W., 44.2ft., with
scribe marks T27S R7W S5 BT visible on partially healed
blaze.

and an accessory established by Powell, Jones, and Penley, in
1970

An iron rod, 5/8" dia., firmly set, projecting 2" above
ground, bears N.12°25'56"W., 23.6 ft.

and new bearing trees

A fir, 9" dia., bears N.31½°E., 18.8 ft., mkd. T26S R7W
S33 BT.

A fir, 10" dia., bears S.17½°E., 10.8 ft., mkd. T27S R7W
S4 BT.

A fir, 13" dia., bears S.25¾°W., 24.4 ft., mkd. T27S R7W
S5 BT.

A fir, 9" dia., bears N.19¾°W., 24.6 ft., mkd. T26S R7W
S32 BT.

Each new bearing tree has a 2½" X ¼". Magnetic nail (MAG-
NAIL) driven at the base right side-center, unless otherwise
described in the corner description.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2306, Surveyed April 2010 - (DCSO
records Vol. 57 Page(s) 22763-4 & Survey plat 2012-1 A&B)

The cor. of secs. 4, 5, 32, & 33, on the S. bdy. of the Tp.,
monumented with an iron post, 2½" dia., firmly set,
projecting 2" above ground, (alongside of which is on iron
pipe, 2½" dia., firmly set, projecting 2" above ground) with
a brass cap (properly) mkd.

from which the remains of the original bearing trees

A sawed fir stump, 33" dia., bears N.75¾°E., 11.9 ft.,
with no marks visible on a partially healed blaze, with
a metal cover.

A sawed fir stump, 34" dia., bears East, 51.5 ft., with no
marks visible.

A sawed fir stump, 20" dia., bears N.64°W., 29.7 ft., with
no marks visible and a metal cover.

and the remains of a BT mkd. by Zirpel and Martin

A sawed fir stump, 29" dia., bears S.68½°W., 44.2 ft.,
with scribe marks T27S R7W S5 BT visible on a partially
healed blaze.

and an accessory established by the Douglas County Surveyor's
Office in 1970

A rebar, 5/8" dia., firmly set, projecting 4" above ground,
bears N.12°25'56"W.. 23.60 ft.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Cor. Secs. 32, 33; 4 & 5 T27-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of bearing trees mkd. by Moore and Browning
A fir, 11" dia., bears N.31½°E., 18.8 ft., with a healed blaze.

A roothole bears S.17½°E., 10.8 ft., downhill of which is a down fir snag, 12" dia., with a healed blaze.

A roothole bears S.25¾°W., 24.4 ft., downhill of which is a down fir snag, 15" dia., with no marks visible.

A fir, 11" dia., bears N.9¾°W., 24.6 ft., with fragmentary scribe marks visible on a partially healed blaze.

and the remains of a reference tree mkd. by person(s) unknown

A sawed, decayed fir stump, size indeterminate, bears S.86¾°W., 33.6 ft., with axe marks visible and a metal tag.

and new bearing trees

A fir, 13" dia., bears S.26¼°E., 22.8 ft.. mkd. T27S R7W S4 BT.

A fir, 5" dia., bears S.52¾°W., 41.7 ft., mkd. X BT.

Corner is located 125 ft. W. of Doerner Road, asphalt surfaced, 22 ft. wide, bears N.10°W. and S.10°E.

From this corner, a point established by Byron, Deputy County Surveyor, in 1970, bears N.88°45'25"E., 1225.91 ft., monumented with a rebar, 5/8" dia., firmly set, flush with ground, and is not utilized during the course of this survey.

(NAD 1983 (CORSS))

Latitude 43°15'28.48" N. Longitude 123°32'42.75"W