

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint, Under Contract #392, dated May 1881
(DCSO records Volume 11 Page 4623)

Set a Cedar post, 3" sq., 3 ft. long, firmly in the ground
for ¼ sec. corner, from which

A Fir 12" dia., bears S.53°E., 7 lks. dist.

A Fir 12" dia., bears S.70°W., 14 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry etal,
Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO records
Volume 37 Page 15175-76)

Point for the 1/4 sec. cor. of secs. 32 and 33, at
proportionate distance; there is no remaining evidence of the
original corner.

Set a Iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the
ground, with brass cap mkd: T 26 S R 7 W

1/4
S 32|S 33
1974

from which

A Fir 6" dia., bears S.32°E., 29 lks. mkd. ¼ S33 BT.

A Fir 13" dia., bears S.70½°W., 59 lks. mkd. ¼ S32 BT.

The corner is located at bottom of descent, slopes N.40°W.

Fd. & used on BLM Dependent resurvey by Timothy J Moore, Cad.
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21014)

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor
and Robert H. Browning, Survey Tech, under Group No. 2140
surveyed June/Aug. 2006- (DCSO records Vol. 57 Page(s) 22481)

The ¼ sec. cor. of secs. 32 and 33, monumented with an iron
pipe, 2½" dia., firmly set, projecting 4" above the ground,
with brass cap (properly) mkd.

from which bearing trees mkd. by Peterson, Berry, Popken, and
Wofford

A fir, 20" dia., bears S.32°E., 19.1 ft., with a healed
blaze.

A fir, 29" dia., bears S.70¼°W., 38.9 ft., with a healed
blaze.

Fd as per ren. D. Edwards - C.S. 65/105-3; set 6' steel post
2' south