

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint Under Contract #392, dated May 1881
(DCSO records Volume 11 Page 4623)

Corner to secs. 28, 29, 32 and 33, from which
A Laurel 5" dia., bears S.40°E., 25 lks. dist.
A Fir 25" dia., bears S.60°W., 28 lks. dist.
A Laurel 5" dia., bears N.70°W., 18 lks. dist.
A laurel 5" dia., bears N.40°E., 27 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry & etal
under Group #'s 744 and 838. Survey May 1971/Aug. 1974
(DCSO records, Volume 37 Page 15176)

Point for the cor. of secs. 28, 29, 32 and 33, at
proportionate distance; there is no remaining evidence of the
original corner.

Set an Iron post, 28" long, 2½" dia., 22" in the ground, with
brass cap mkd.

T 26 S R 7 W
S 29 | S 28
S 32 | S 33

from which

- A Madrone 6" dia., bears N.69°E., 97 lks. dist.
mkd. T26S R7W S28 BT.
- A Fir 10" dia., bears S.5°E., 160 lks. dist., mkd.
T26S R7W S33 BT.
- A Fir 12" dia., bears S.32°W., 88 lks. dist., mkd.
T26S R7W S32 BT.
- A Fir 9" dia., bears N.40°W., 129 lks. dist., mkd.
T26S R7W S29 BT.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21014-5)

The cor. of secs. 28, 29, 32, and 33, monumented with an iron
post, 2½" dia., firmly set, projecting 5" above ground, with
brass cap (properly) mkd.

from which BTs mkd. by Peterson, Berry, Popken, and Wofford

- A fir, 19" dia., bears S.5°E., 105.6 ft., with a healed
blaze.
- A fir, 23" dia., bears S.32°W., 58.1 ft., with a healed
blaze.
- A fir, 20" dia., bears N.40¼°W., 85.1 ft., with a healed
blaze.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a new bearing tree

A fir, 7" dia. bears N.60°E., 7.5 ft. mkd. T26S R7W S28 BT
Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL)
driven at the base right side-center, unless otherwise
described in the corner description

FD. BC & 4 BTs by Ken Hoffine - Oct. 2009 - M160-19

Fd. Ok by D. Edwards, 7/2014 - M168-24

Fd as per M160-19 D. Edwards - C.S. 65/105-3; set 6' steel
post 2' south