

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - S.C. Flint, Under Contract #392, dated May 1881  
(DCSO records Volume 11 Page 4624)

-----  
Set ¼ sec. post, a Laurel, 3 ft. long, 3" sq., firmly  
in the ground, from which

A Laurel 4" dia., bears N.65°W., 8 lks dist.

A Laurel 6" dia., bears S.25°E., 33 lks. dist.

-----  
Bureau of Land Management resurvey by Peterson, Berry, etal,  
Group #'s 744 & 838, Survey May 1971/Aug. 1974 (DCSO records  
Volume 37 Pages 15178-79)

-----  
Point for the 1/4 cor., at proportionate distance; there is no  
remaining evidence of the original corner.

Set an Iron post, 28" long, 2½" dia., 22" in the ground, with  
brass cap marked: T 26 S R 7 W

1/4

S 29 | S 28

1974

from which

A Fir 7" dia., bears S.30¾°E., 14 lks., mkd. ¼ S28 BT.

A Fir 6" dia., bears N.74½°W., 23 lks., mkd. ¼ S29 BT.

-----  
Fd. OK, BLM Dependent resurvey by Timothy J. Moore, Cadastral  
Surveyor & Robert Browning, Surveying Technician under Group  
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21015)

-----  
Fd. BC & 2 BTs by Ken Hoffine - Oct. 2009 - M160-19