

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, under Contract #392 dated May 26, 1881 - (DCSO records, Volume 11 Page 4624)

Set a Cedar post 40" long and 4" sq. firmly in the ground, from which

- A Fir 36" dia., bears S.25°E., 6 lks. dist.
- A Fir 14" dia., bears N.85°E., 30 lks. dist.
- A Fir 36" dia., bears N.40°W., 46 lks. dist.
- A Fir 36" dia., bears S.35°W., 65 lks. dist.

BLM resurvey by Zirpel and Martin, Group #'s 350 & 357 Survey, April/May 1959 (DCSO records, Vol. 29 Pg. 12538)

Point for corner, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 12" in the ground, to bedrock, & in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T26S R7W
S 20 | S 21
S 29 | S 28
1959

from which

- A bedrock outcropping chiseled X BT, bears S.70°E., 11½ lks. dist.
- A Madrone 6" dia., bears S.39°W., 11 lks. dist., bark scribed T26S R7W S29 BT.

No other suitable bearing trees are available.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

Bureau of Land Management resurvey by Peterson, Berry, et al, Under Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO Records, Vol. 37 Page 15179)

The corner is monumented with an iron post, 2½" dia., firmly set in a mound of stone, 3 ft. base, 1½ ft. high, with brass cap mkd.

T 26 S R 7 W
S 20 | S 21
S 29 | S 28
1959

from which a bearing object mkd. by Zirpel and Martin in 1959

- A bedrock outcropping, chiseled X BT, bears S.70°E., 11½ lks. dist.

and a new bearing tree

- A Madrone 8" dia., bears S.39°W., 11 lks. dist.

No other suitable trees available within limits.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21015-6)

The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, loosely set, projecting 18" above ground, reset in a mound of stone, 3½ ft. base, 1½ ft. high, with brass cap mkd. from which a bearing object mkd. by Zirpel and Martin

A bedrock outcropping, bears S.70°E., 7.6 ft., chiseled X BO.

and a BT mkd. by Peterson, Berry, Popken, and Wofford

A madrone, 12" dia., bears S.39°W., 7.3 ft., with no marks visible.

and a new bearing tree

A fir, 18" dia., bears N.47½°W., 75.3 ft., mkd. T26S R7W S20 BT.

No other suitable trees available in sec. 21, within limits. Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68

BLM retracement & rehabilitation by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2300, surveyed March 2009 - (DCSO records Vol. 56 Page 22270 & BLM Plat T26-7 2011-2)

The cor. of secs. 20, 21, 28, & 29, monumented with on iron post, 2½" dia., firmly set, projecting 4" above a mound of stone, 3½ ft base, 1½ ft high, with brass cap (properly) mkd. from which a bearing object mkd. by Zirpel and Martin, reported by Moore and Browning

A bedrock outcropping, bears S.70°E., 7.6 ft., chiseled X BO.

and a bearing tree mkd. by Peterson, Berry, Popken, and Wofford, reported by Moore and Browning

A madrone, 13" dia., bears S.39°W., 7.3 ft., with no marks visible.

and a bearing tree mkd. by Moore and Browning in 2001

A fir, 21" dia.. bears N.47½°W., 75.3 ft., with a healed blaze.

and a new bearing tree

A madrone, 6" dia., bears N.55¼°E., 12.3 ft., mkd. T26S R7W S21 BT.