

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - S. C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 11 Page 4625)

Set a Laurel ¼ post, 36" long, 4" sq., from which
A Laurel 16" dia., bears N.70°E., 57 lks. dist.
A Fir 18" dia., bears N.30°W., 89 lks. dist.

Bureau of Land Management resurvey by Zirpel and Martin under Group #'s 350 and 357, Survey April/May 1959 (DCSO Records, Volume 29 12539)

Point for the ¼ corner, at proportionate distance; there is no remaining evidence of the original corner.
Set a brass tablet, 3½" dia., 3½" stem, in a drilled hole in bedrock, marked:
T26S R7W
¼
S 20|S 21
1959

from which
A Fir 16" dia., bears S.60°E., 78 lks. mkd. ¼ S21 BT.
A Fir 14" dia., bears N.52°W., 140 lks. mkd. ¼ S20 BT.

Fd Ok BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21029)

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68