

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S. C. Flint, Under Contract #392 dated May 26, 1881 (DCSO records, Volume 11 Page 4625)

Set post, Laurel, 40" long, 4" sq., from which
A Fir 6" dia., bears S.85°W., 6 lks. dist.
A Laurel 10" dia., bears S.65°E., 7 lks. dist.
A Fir 10" dia., bears N.10°E., 16 lks. dist.
A Laurel 10" dia., bears N.25°W., 32 lks. dist.

Bureau of Land Management resurvey by Zirpel and Martin, under Contract #'s 350 and 357. Survey April/May 1959 (DCSO records Volume 29 Pages 12539-40)

Corner determined at record distance from each of the remaining original bearing trees:
A Fir 25" dia., bears N.16°E., 16 lks. dist. with a healed blaze. (Rec. Bearing, N.10°E.)
The stump hole of a Fir that has been dozed out, bears S.85°W., 6 lks. dist. The tree is lying alongside the stump hole and is burned & rotted Fir, 8" dia., with illegible scribe marks visible on an opened blaze.

At the corner point, Set an Iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

T26S	R7W
S 17	S 16
S 20	S 21
1959	

from which
A Fir 11" dia. bears S.16¼°E., 120½ lks. dist. mkd.
T26S R7W S21 BT.
A Fir 14" dia. bears S.71¾°W., 133 lks. dist. mkd.
T26S R7W S20 BT.
A Fir 10" dia., bears N.13¼°W., 91 lks. dist., mkd.
T26S R7W S17 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack Heritage - May/June 1966 - C.S. File 54/23-20

Found - 1959 Cadastral brass cap appropriately marked.
11" Fir S.16¼°E., 79.5 ft., now snag 25.0 ft. high, shows "T26S R7W S21 BT" scribe on unhealed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

14" Fir S.71 $\frac{3}{4}$ °W., 87.8 ft., alive, shows scribe on unhealed blaze.
10" Fir N.13 $\frac{3}{4}$ °W., 60.1 ft., now turned out, laying face down.
Original BTs also turned out.
New BTs - 16" W.Fir N.5°W., 110.2 ft. mkd. T26S R7W S20 CS BT.
16" W.Fir S.51°E., 71.4 ft. mkd. T26S R7W S21 CS BT.
No tree convenient to NE.
Corner lies approx. 500 ft. North of old logging road.

BLM resurvey by Peterson Berry, etal under Group #'s 744 & 838 Survey May 1971/Aug. 1974 (DCSO recs Volume 37 Pages 15180-81)

Corner monumented with an iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 4" above ground with 1959 brass cap. from which the remains of the original bearing trees
A root hole, bears N.10°E., 16 lks. dist., with a down fir alongside, 25" dia., with healed blaze. (Record, N.16°E.)
and the remains of the BTs by Zirpel and Martin, in 1959
A Fir snag, 11" dia., bears S.16 $\frac{1}{4}$ °E., 120 $\frac{1}{2}$ lks., with scribe marks T26S R7W S21 BT.
A Fir 17" dia., bears S.71 $\frac{3}{4}$ °W., 135 lks., with scribe marks T26S R7W S20 BT visible on open blaze. (Record, 133 lks.)
A root hole bears N.13 $\frac{3}{4}$ °W., 91 lks., with a down fir alongside, 11" dia., with scribe marks T26S R7W S17 BT visible on open blaze.
and bearing trees mkd. by Tracy, in 1966
A Fir 18" dia., bears S.51°E., 108 lks., with fragmentary scribe marks visible on open double blaze.
A Fir 19" dia., bears N.5°W., 167 lks., with fragmentary scribe marks visible on open double blaze.
and a new bearing tree
A Fir 8" dia. bears N.60°E., 67 lks. mkd. T26S R7W S16 BT

David Edwards - For: Seneca Jones - 1/2002 - C.S. File 65/41-2

Found - BLM brass cap.
16" Fir bears N.60°E., 44.2'
24" Fir bears S.71 $\frac{3}{4}$ °W., 89.1'
19" Fir bears N.5°W., 110.2'
New BT - 14" Fir S.89°E., 14.8' scribed "S21 BT"

Fd. Ok by Lloyd Tolbert, May 2005 - M147-68