

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - S.C.. Flint, Under Contract #392, dated May 1881  
(DCSO records Volume 11 Page 4626)

-----  
Set a Fir post for ¼ sec. cor., 36" long, 3" sq., from which  
A Fir 12" dia., bears S.40°W., 35 lks. dist.  
A Fir 20" dia., bears N.85°E., 16 lks. dist.

BLM resurvey by Roseberry & Garrison under Group #357. Survey  
June/Aug. 1967 (DCSO records, 14282)

-----  
From the 1/4 sec. cor. of secs. 16 and 17, determined at  
record bearing and distance from the remaining original  
bearing tree:

A decayed fir snag 15" dia., bears S.40°W., 35 lks. with  
scribe marks ¼S visible on bark.

At the corner point

Set an Iron post, 28" long, 2½" dia., 24" in the ground, with  
brass cap mkd: T 26 S R 7 W

¼  
S 17|S 16  
1967

from which new bearing trees

A Fir 53" dia., bears S.36°E., 46 lks., mkd. 1/4 S16 BT.

A Fir 45" dia., bears S.72°W., 52 lks., mkd. 1/4 S17 BT.

David Edwards - For: Seneca Jones - 1/2002 - C.S. File 65/41-2

-----  
Found - BLM brass cap.  
45" dia., high stump Fir W/metal cap bears S.72°W.,  
34.3'

New BTs - 26" Cedar N.48°E., 23.4'  
10" W.Fir S.75°E., 19.4'  
Steel fence post south 2.2'  
New BTs scribed ¼ S16 BT.

Fd. Ok by D. Edwards, 7/2005 - C.S. File 65/55-6