

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint under Contract #392 dated May, 1881
(DCSO records, Volume 11 Page 4627)

Set a Cedar post, 40" long, 4" sq., firmly in the ground,
from which

- A W.Fir 24" dia., bears N.10°E., 52 lks..
- A Fir 40" dia., bears S.60°W., 34 lks.
- A Fir 30" dia., bears S.80°E., 34 lks.
- A Fir 6" dia., bears N.60°W., 10 lks.

Bureau of Land Management resurvey by Roseberry & Garrison
under Group #357. Survey June/Aug. 1967 (DCSO records,
Volume 34 Page 14283)

Point for the section cor. at proportionate distance; there
is no remaining evidence of original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:

T 26 S R 7 W
 S 8 | S 9
 S 17 | S 16
 1967

from which

- A Fir 20" dia., bears N.50½°E., 107 lks., mkd. T26S R7W
S9 BT.
- A Fir 42" dia., bears S.52½°E., 25 lks., mkd. T26S R7W
S16 BT.
- A Fir 37" dia. bears S.20°W. 63 lks. mkd. T26S R7W S17 BT
- A Fir 25" dia., bears N.36¼°W., 79 lks., mkd. T26 S R7W
S8 BT.

Fd. Ok by D. Edwards, 7/2005 - C.S. File 65/55-6

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert H. Browning, Surveying Tech. under Group
#2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22083)

The cor. of secs. 8, 9, 16, & 17, monumented with an iron
post, 2½" dia., firmly set, projecting 4" above the ground,
with brass cap (properly) mkd.

from which bearing trees mkd. by Roseberry and Garrison

- A fir, 34" dia., bears N.50½°E., 70.6 ft., with a healed
blaze.
- A fir, 54" dia., bears S.52½°E., 16.5 ft., with a healed
blaze.
- A fir, 46" dia., bears S.20°W., 41.6 ft., with a healed
blaze.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 30" dia., bears N.36¼°W., 52.1 ft., with a healed blaze.

The geographic position (NAD 1983 (CORS)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System Stations noted above, is as follows:

The corner of sections 8, 9, 16, and 17.
Latitude: 43°18'58.19"N. Longitude: 123°32'42.27"W.