

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - S. C. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 11 Page 4628)

Set a Fir post for 1/4 sec. cor., 3 ft. long and 3" sq., from which

A Fir 24" dia., bears N.10°W., 13 lks. dist.

A Hemlock 6" dia., bears N.45°E., 30 lks. dist.

Bureau of Land Management resurvey by Roseberry & Garrison under Group #357. Survey June/Aug. 1967 (DCSO records, Volume 34 Page 14285)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an Iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T 26 S R 7 W

1/4

S 8 | S 9

1967

from which

A Fir 14" dia., bears N.46°E., 31 1/2 lks. dist., mkd.

1/4 S9 BT.

A Fir 23" dia., bears S.25°W., 32 lks. dist., mkd.

1/4 S8 BT.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flauser - Oct. 16, 1997 - C.S. 64/78-17

Mon. Fd.- 3 1/2" dia. Brass cap on a 2 1/2" O.D. iron pipe protrudes 8" above ground.

BT's Fd.- 23" now 28" dia. D.Fir, with a fully healed single blaze, bears S.25°W., 21.1' (agrees with rec.) 1967.

14"? now 52" dia. D.fir, with a fully healed single blaze, bears N.46°E., 20.8' (agrees with rec.) 1967.

New Accessories -

Grown together 20" dia. R.Cedar, double blazed and scribed "1/4 S8 CS BT" on southerly trunk, root crown bears N.65°W., 8.3'.

6" dia. Grand Fir, double blazed and scribed "1/4 S9 CS BT", bears S.65°E., 12.3'.

Corner is approx. 200' east from abandoned logging spur road. Old growth trees stand in northeast quadrant cutting line run north and north 45° East.

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy Moore, Cadastral Surveyor & Robert H Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pgs 22083-4)

The ¼ sec. cor. of secs. 8 & 9, monumented with an iron post, 2½" dia., firmly set, projecting 8 ins. above the ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Roseberry and Garrison

A fir, 53" dia., bears N.46°E., 20.8 ft., with a healed blaze.

A fir, 30" dia., bears S.25°W., 21.1 ft., with a healed blaze.

and BTs mkd. by the Douglas County Surveyors Office, in 1997

A fir, 8" dia., bears S.64¾°E., 12.1 ft., with a healed double blaze.

A double trunked cedar, 23" dia., bears N.67°W., 8.3 ft., with fragmentary scribe marks 1/4 S8 CS visible on partially healed blaze.