

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4616)

-
- Marked a Maple, 4" dia., for corner, from which
- A Fir 4" dia., bears S.55°W., 3 lks. dist.
 - A Fir 6" dia., bears S.85°E., 40 lks. dist.
 - A Chinquapin 8" dia., bears N.65°E., 16 lks. dist.
 - A circular rock, 25 ft. in diam., and 8 ft. high mkd.
 - X on side facing cor. bears N.55°W., 7 lks.

GLO survey by S.C. Flint, under Contract #392, dated May 26, 1881 - (DCSO records 4628)

-
- Cedar post, 40" long, 3" sq., set firmly in the ground, from which
- A Fir 10" dia., bears S.80°W., 10 lks. dist.
 - A Fir 12" dia., bears N.20°W., 14 lks. dist.
 - A Fir 6" dia., bears S.5°E., 34 lks. dist.
 - A Fir 8" dia., bears N.45°E., 59 lks. dist.

Bureau of Land Management resurvey by Roseberry & Garrison under Group #357. Survey Jan/Aug. 1967 (DCSO records, Volume 34 Pages 14285-86)

-
- The cor. established by Flint in 1881, determined from the original bearing trees:
- A Fir 22" dia., bears N.37³/₄°E., 48 lks dist. with axe marks visible on opened blaze. (Rec. N.45°E., 59 lks.)
 - A decayed Fir stump 8" dia., bears S.5°E., 34 lks. dist. with old axe marks visible.
 - A root hole bears S.80°W., 10 lks. dist., with a fallen Fir alongside, 16" dia., with opened and rotted blaze, no scribe marks visible.
 - A Fir 30" dia., bears N.20°W., 14 lks. dist., with scribe marks BT visible on partially opened blaze.

At the corner point, Set an Iron post, 28" long, 2½" dia., 14" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 26 S R 7 W
 S 5 | S 4
 S 8 | S 9
 1967

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which new bearing trees

A Fir 16" dia. bears N.78¼°E. 54½ lks. mkd. T26S R7W S4 BT

A Cedar 7" dia. bears S.78½°E., 40 lks. mkd T26S R7W S9 BT

A Cedar 11" dia. bears S.72°W., 41½ lks mkd T26S R7W S8 BT

From this point, the cor. established by Hathorn in 1855, bears N.17°W., 0.195 chs. dist., determined at record bearing and distance from the remaining original bearing tree and object:

A decayed Fir stump, 4" dia., bears S.55°W., 3 lks., with fragmentary scribe marks visible on rotted blaze.

A circular rock, 25 ft. dia., 8 ft. high, bears N.55°W., 7 lks., mkd. with a cross (X) on the side facing the corner.

The 1855 Hathorn corner is superseded by the 1881 Flint cor.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22085)

The cor. of secs. 4, 5, 8, and 9, monumented with an iron post, 2½" dia., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base to top, with brass cap (properly) mkd. from which the remains of original bearing trees

A sawed fir stump, 25" dia., bears N.37¾°E., 31.7 ft., with no scribe marks visible on opened blaze.

A fir, 38" dia., bears N.20°W., 9.2 ft., with no scribe marks visible on opened blaze.

and the remains of BTs mkd. by Roseberry and Garrison

A sawed fir stump, 24" dia., bears N.76½°E., 36.0 ft., with a healed blaze. (Record, N.78¼E.)

A cedar snag, 10" dia., bears S.78½°E., 26.4 ft., with scribe marks R7W S9 BT visible on partially healed blaze.

A cedar, 20" dia., bears S.72°W., 27.4 ft., with fragmentary scribe marks visible on partially healed blaze.

and new bearing trees

A cedar, 7" dia., bears N.41¼°E., 39.2 ft., mkd. X BT.

A fir, 5" dia., bears S.36½°E., 19.2 ft., mkd. X BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

There is no longer any evidence of the corner established by Hathorn, in 1855.

Corner is located on a NE. slope, with numerous large rock outcroppings.