

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - S.C. Flint, Under Contract #392 dated May 1881  
(DCSO records Volume 11 Page 4629)

-----  
Set Laurel post for 1/4 sec. cor., 3 ft. long 3 ins. sq.,  
from which

A Fir 30" dia., bears S.85°E., 45 lks. dist.

A Cedar 50" dia., bears N.20°W., 46 lks. dist.

-----  
F.C. Frear; N.E. Richardson; P.D. Wolford - June 1934  
(No source record found, see "old" renewal book, Page 76)

-----  
Set 4" x 4" x 30" Fir stake from old BT and marked new  
BTs as follows:

Fir 24" dia., bears N.86°E., 24 ft.

Fir 24" dia., bears S.49°E., 22.3 ft.

-----  
Not Found, V. Tracy, Jan. 23, 1968

-----  
R.E. Stuntzner Engineering, for: Reservation Ranch, Feb. 25,  
1974 - M 52-50

-----  
Set - 5/8" Iron rod for 1/4 corner, from which  
8" Cedar, N.33°E., 35.5 ft.  
18" Fir, west 7.4 ft.

I find no remaining evidence of the remonumentation in the  
1930's.