

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C Flint, Under Contract #392, dated May 1881
(DCSO records Volume 11 Page 4624)

Set a Hemlock post for ¼ sec. post, from which
A Laurel 12" dia., bears S.12°W., 30 lks. dist.
A Fir 15" dia., bears N.15°E., 12 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal,
Group #'s 744 & 838. Survey May 1971/Aug. 1974 (DCSO
records, Volume 37 Page 15178)

Point for the 1/4 sec. cor., at proportionate distance; there
is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 22" in the ground,
with brass cap mkd. T 26 S R 7 W

¼ $\frac{S\ 28}{S\ 33}$
1974

from which
A Fir 8" dia., bears N.76°E., 48 lks. mkd. 1/4 S28 BT.
A Fir 6" dia., bears S.17½°W., 6½ lks. mkd. 1/4 S33 BT.

Fd. BC & 2 BTs by Ken Hoffine - Oct. 2009 - M160-19

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor and Robert H. Browning, Survey Tech, under Group No.
2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Pg 22472)

The ¼ sec. cor. of secs. 28 & 33, monumented with an iron
post, 2½" dia., firmly set, projecting 6" above the ground,
with brass cap (properly) mkd.

from which bearing trees mkd. by Peterson, Berry, Popken, and
Wofford

A fir, 17" dia., bears N.76°E., 31.7 ft., with a healed
blaze.

A fir, 21" dia., bears S.11¼°W., 4.3 ft., with a healed
blaze. (Record, S.17½°W.)

Fd. BC & BT per M160-16 SET 6' steel post 2 ft. East 10/2015
by D. Edwards