

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 21 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint, Under Contract #392, dated May 1881
(DCSO records Volume 11 Page 4625)

Set a Cedar 1/4 post, 3" sq. and 36" long, firmly in the
ground, from which

A Fir 36" dia., bears S.85°W., 4 lks. dist.

A Fir 20" dia., bears N.85°E., 57 lks. dist.

Bureau of Land Management resurvey by Zirpel and Martin
under Group #'s 350 and 357. Survey April/May 1959
(DCSO records, Vol. 29 Page 12537)

Point for the 1/4 cor., at proportionate distance; there is
no remaining evidence of the original corner.

Set an Iron post, 28" long, 2 1/2" dia., 24" in the ground, with
brass cap mkd. T26S R7W

1/4 S 21
S 28
1959

from which

An Iron post, 28" long, 2 1/2" dia., set 24" in the ground,
for a reference monument, bears North, 11 1/4
lks. dist., with brass cap marked T26S R7W 1/4 S21 RM
1959 and an arrow pointing to the corner.

An Iron post, 28" long 2 1/2" dia., set 24" in the ground,
for a reference monument, bears South 11 1/4 lks.
dist., with brass cap mkd. T26S R7W 1/4 S28 RM 1959
and an arrow pointing to the corner.

No suitable bearing trees are available.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21017)

Fd. BC & 2 RMs Ken Hoffine - Oct. 2009 - M160-19

BLM retracement & rehabilitation by A. Bert Skeesick,
Cadastral Surveyor, under Group No. 2300, surveyed March 2009
- (DCSO records Vol. 56 Page 22270 & BLM Plat T26-7 2011-2)

The 1/4 sec. cor. of secs. 21 & 28, monumented with an iron
post, 2 1/2" dia., firmly set, projecting 8" above the ground,
with brass cap (properly) mkd.

from which reference monuments set by Zirpel and Martin,
reported by Moore and Browning

continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An iron post, 2½" dia., firmly set, projecting 4" above the ground for a reference monument, bears S.3°21'18"E. 7.4 ft. with brass cop mkd. T26S R7W ¼ S28 RM 1959 and an arrow pointing to the corner.
An iron post, 2½" dia., firmly set, projecting 9" above the ground for a reference monument, bears N.1°25'18"W. 7.4 ft. with brass cap mkd. T26S R7W ¼ S21 RM 1959 and an arrow pointing to the corner.
Latitude 43°17'13.59"N. Longitude 123°32'41.99"W.
(NAD 1983)

Fd. Ok by D. Edwards, 7/2014 - M168-24
Fd. as per record by K Hoffine, 3/2016 - M170-67