

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21027)

Point for the center ¼ sec. cor. of sec. 21, at the intersection with the E. & W. centerline.
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T 26 S R 7 W
C 1/4 S 21
2001

from which
A fir, 6" dia., bears S.52½ E., 4.4 ft., mkd. C¼ S21 BT.
A fir, 12" dia., bears S.76½°W., 2.8 ft., mkd. C¼ S21 BT.
Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, a point unofficially established as the center ¼ sec. cor. of sec. 21 by the Bureau of Land Management, in 1978, during the course of an administrative survey, bears N.23°36'23"E., 1.17 ft., monumented with a galvanized iron pipe, ½" dia., firmly set, projecting 4" above ground. This point was not utilized during the course of this survey. Remove the iron pipe and place inside the stainless steel post, from which unmarked bearing trees referenced to in the administrative survey
A fir, 12" dia. bears S.54¾°E. 12.4 ft. w/no marks visible
A fir, 13" dia. bears N.30¾°W. 2.1 ft. w/no marks visible