

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - S.C. Flint, Under Contract #392, dated Ma7 1881
(DCSO records Volume 11 Page 4626)

Set a Cedar post for ¼ sec. cor. 3 ft. long and 3" sq.,
from which

A Fir 12" dia., bears N.25°E., 26 lks. dist.

A Fir 12" dia., bears S.40°E., 27 lks. dist.

BLM resurvey by Peterson, Berry, etal, under Group #'s 744 &
838. Survey 1971/1974 (DCSO records, Volume 37 Page 15180)

Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate
distance; there is no remaining evidence of the original cor.
Set an Iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd:

T 26 S R 7 W

1/4 $\frac{S\ 16}{S\ 21}$

1974

from which

A W.Fir 21" dia., bears N.51°E., 97 lks. mkd. 1/4 S16 BT.

A Fir 19" dia., bears S.39°W., 67 lks. mkd. 1/4 S21 BT.

David Edwards - For: Seneca Jones - 1/2002 - C.S. File 65/41-2

Found - BLM brass cap.

25" Fir bears N.51°E., 64.02'

4" Fir bears S.4°E., 49.0'

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21018-9)

The ¼ sec. cor. of secs. 16 & 21, monumented with an iron
post, 2½" dia., firmly set, projecting 4" above ground, with
brass cap (properly) mkd.,

from which the remains of BTs mkd. by Peterson, Berry,
Popken, and Wofford

A fir, 28" dia., bears N.51°E., 64.0 ft., with a healed
double blaze.

A decayed fir snag, 19" dia., bears S.39°W., 44.2 ft.,
with a healed blaze.

and a new bearing tree

A fir, 4" dia., bears S.3¾°E., 49.2 ft., mkd. X BT.

Corner is located at the base of a fir, 27" dia.

Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL)
driven at the base right side-center, unless otherwise
described in the corner description