

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 9 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12 1855 (DCSO records, Volume 11 Page 4615)

Set ¼ sec. post, from which
 A Fir 16" dia., bears N.10°E., 75 lks. dist.
 A Fir 14" dia., bears S.85°E., 35 lks. dist.

GLO survey by S.C. Flint, under Contract #392 dated May 26, 1881 (DCSO records, Volume 11 Page 4627)

Set a Laurel post for ¼ sec. cor., 3 ft. long, 3" sq., from which
 A Fir 20" dia., bears N.60°W., 57 lks. dist.
 A Fir 18" dia., bears S.30°W., 70 lks. dist.

Bureau of Land management resurvey by Roseberry & Garrison under Group #357. Survey June/Aug. 1967 (DCSO records, Volume 34 Page 14284)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd:
 T 26 S R 7 W
 ¼ S 9
 S 16
 1967

from which
 A Fir 9" dia., bears N.63½°W., 53 lks., mkd. ¼ S9 BT.
 A Fir 12" dia., bears S.18°E., 48 lks., mkd. ¼ S16 BT.
From this point, the ¼ sec. cor. of secs. 9 and 16, established by Hathorn in 1855, bears S.46°30'W., 0.84 chs. dist., determined at record bearing and distance from the remaining original bearing tree:
 A sawed Fir stump 28" dia., bears S.85°E., 35 lks., with scribe mark S visible on bark.
This 1855 Hathorn corner is superseded by the 1881 Flint survey of the mile between secs. 9 and 16.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor & Robert H Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pg 22082)

The ¼ sec. cor. of secs. 9 & 16, monumented with an iron post, 2½" dia., firmly set, projecting 13" above the ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Roseberry and Garrison continued next page

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 9 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 24" dia., bears S.16 $\frac{1}{4}$ °E., 29.6 ft., with a healed blaze. (Record, S.18°E., 31.7 ft.)

A fir, 22" dia., bears N.63 $\frac{1}{2}$ °W., 35.0 ft., with a healed blaze.

From this corner, a point established as the $\frac{1}{4}$ sec. cor. of secs. 9 & 16, by Hathorn in 1855, bears S.47°45'17"W., 56.74 ft., (record, S.46°30'00"W., 55.44 ft.), determined at record bearing and distance from the remaining original bearing tree: (the Hathorn position was superseded by the 1881 Flint survey)

A sawed fir stump, 26" dia., bears S.85°E., 23.1 ft., no marks visible.