TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4616)

Set ¼ sec. post, from which
A Fir 14" dia., bears S.25°W., 54 lks. dist.
A Maple 10" dia., bears N.45°W., 79 lks. dist.

GLO survey by S.C. Flint, under Contract #392 dated May 1881 (DCSO records, Volume 11 Page 4628)

Set Fir post for ¼ se. cor., 3 ft. long, 3" sq., from which
An Alder 24" dia., bears North, 6 lks. dist.
An Alder 8" dia., bears S.20°W., 31 lks. dist.

Bureau of Land Management resurvey by Roseberry & Garrison under Group #357. Survey June/Aug. 1967 (DCSO records, Volume 34 page 14287)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an Iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd: T 26 S R 7 W

¼ S 4 / S 9

1967

from which
A fir 18" dia., bears N.16°E., 77½ lks., mkd. ¼ S4 BT.
A Fir 40" dia., bears S.12°E., 77½ lks., mkd. ¼ S9 BT.

BLM Dependent resurvey by Timothy Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2075, surveyed April/June 2005 (DCSO rec. Vol. 56 pgs 22086-7)

The ¼ sec. cor. of secs. 4 & 9, monumented with an iron post, 2½" dia., firmly set, projecting 9 ins. above the ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Roseberry and Garrison
A sawed fir stump, 22" dia., bears N.16°E., 51.2 ft., no marks visible.
A root hole, bears S.12°E., 51.2 ft., alongside of which is the fir trunk, 38" dia., with a healed blaze.
and new bearing trees
A fir, 7" dia., bears N.45°E., 10.4 ft., mkd. ¼ S4 BT.
A fir, 5" dia., bears S.14¼°E., 9.8 ft., mkd. 1/4 S9 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.