

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Pages 4608-09)

Set 1/4 sec. post, from which
 A B.Oak 10" dia., bears S.62°W., 105 lks. dist.
 A B.Oak 10" dia., bears S.52°E., 127 lks. dist.

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records Volume 37 Pages 15168-69)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set a iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd:
 T 26 S R 7 W
 1/4
 S 33|S 34
 1974

from which
 An Oak, 10" dia., bears N.83°W., 75 lks., mkd. 1/4 S33 BT.
No other suitable trees available within limits.

Fd. Ok by Mark Heimburger - 10/1998 - M 130-72

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Pg 22469)

The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford in 1971-74
 A sawed oak stump, 22" dia., bears N.83°W., 49.5 ft., with a healed blaze.

and new accessories
 An iron rod, 30" long, 5/8" dia., driven 27" in the ground for a reference monument bears N.32°04'11"E. 8.1 ft., with aluminum cap mkd. RM 1/4 S34 8.1 FT TO COR 2006, and an arrow pointing to the corner.
 An iron rod, 30" long, 5/8" dia., driven 26" in the ground for a reference monument bears N.34°28'51"W. 8.0 ft., with aluminum cap mkd. RM 1/4 S33 8.0 FT TO COR 2006, and an arrow pointing to the corner.

The 1/4 sec. corner of sections 33 & 34. (NAD 1983 (CORS 96))
Latitude: 43°15'55.25"N Longitude: 123°31'31.57"W