

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4609)

Set post cor. secs. 27, 28, 33 and 34, from which

- An Alder 4" dia., bears N.18°W., 10 lks. dist.
- An Alder 6" dia., bears S.60°W., 46 lks. dist.
- An Alder 6" dia., bears S.35°E., 46 lks. dist.
- A Fir 20" dia., bears N.88°E., 206 lks. dist.

Bureau of Land Management resurvey by Peterson, Berry, etal, Group #'s 744 and 838 Survey May 1971/Aug. 1974 (DCSO records Volume 37 Page 15169)

Point for the cor. of secs. 27, 28, 33 & 34, at proportionated distance; there is no remaining evidence of the orig. corner. This point is located in a beaver pond, where it is impracticable to establish a permanent monument.

(Pages 15176-77)

Point selected for the witness corner of secs. 27, 28, 33, and 34. Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd.

W C	
T 26 S R 7 W	
S 28 S 27	→
S 33 S 34	

from which

- A Madrone 6" diam., bears N.3°E., 48 lks. mkd. X BT.

No other suitable trees available within limits.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2140 surveyed June/Aug. 2006- (DCSO records Vol. 57 Pg 22470)

The witness cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2½" dia., firmly set, 10" below the surface of the water, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Peterson, Berry, Popken, and Wofford

- A sawed madrone stump, 8" dia., bears N.3°E., 31.7 ft. no marks visible.

No new accessories available within limits.