

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4610)

-----  
Set 1/4 sec. post, from which  
    A Laurel 12" dia., bears S.55°W., 11 lks. dist.  
    A Laurel 10" dia., bears N.35°E., 56 lks. dist.

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838, Survey May 1971-Aug. 1974 (DCSO records Volume 37 Page 15171)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd:

T 26 S R 7 W  
    1/4  
    S 28 | S 27  
    1974

from which  
    A Madrone 15" dia., bears S.53 1/2°E., 75 lks. mkd. 1/4 S27 BT  
    A Fir 8" dia., bears S.83°W., 95 1/2 lks. mkd. 1/4 S28 BT.

Fd. BC & 2 BTs by Ken Hoffine - Oct. 2009 - M160-19