

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4610)

Set post cor. secs. 21, 22, 27 and 28, from which
A Laurel 15" dia., bears S.16°E., 30 lks. dist.
A Fir 10" dia., bears S.82°W., 26 lks. dist.
A Chinquapin 8" dia., bears N.25°E., 35 lks. dist.
A Maple 10" dia., bears N.20°W., 82 lks. dist.
A rocky bluff, 200 ft. high bears W. about 2 chs.

Bureau of Land Management resurvey by Irving Zirpel and Leo Martin under Group #'s 350 and 357. Survey in 1959 (DCSO records, Volume 29 Pages 12536)

Corner determined at record distance from each of the remaining original bearing trees:
The stump of a burned and rotted madrone with small sprouts, bears S.16°E., 30 lks. dist.
A rotted and burned Fir stump, approx. 20" dia., bears S.85°W., 26 lks. dist. (Rec. bearing S.82°W.)
A rotted and burned Maple stump 21" dia., with small sprouts, bears N.20°W., 82 lks. dist.
At the corner point, set an iron post, 28" long 2½" dia., 26" in the ground, with brass cap mkd. T26S R7W
S 21 | S 22
S 28 | S 27
1959
Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
No suitable bearing trees available.

Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records Volume 37 Page 15172)

The cor. of secs. 21, 22, 27 and 28, monumented with an iron post 2½" dia., firmly set, projecting 6" above ground, with brass cap properly mkd.
from which the remains of an original bearing tree
A decayed and burned Fir stump 20" dia., bears S.85°W., 26 lks. dist., with old axe marks visible on decayed face.
and new bearing trees
A Fir 6" dia., bears N.40½°E., 22 lks. dist.
mkd. T26S R7W S22 BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 8" dia., bears S.89½°E., 10½ lks. dist.,
mkd. T26S R7W S27 BT.
No other suitable trees available within limits.
Add marks 1974 to brass cap.

BLM Dependent resurvey by Timothy J. Moore, Cadastral
Surveyor & Robert Browning, Surveying Technician under Group
#1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21011-2)

The cor. of secs. 21, 22, 27, & 28, monumented with an iron
post, 2½" dia., firmly set, projecting 5" above ground, with
brass cap (properly) mkd.
from which the remains of an original bearing tree
A stump hole, bears S.16°E., 19.8 ft., with madrone
sprouts, 8" dia., with no marks visible.
and bearing trees mkd. by Peterson, Berry, Popken, and Wofford
A fir, 14" dia., bears N.40½°E., 14.5 ft., with a healed
blaze.
A fir, 17" dia., bears S.89½°E., 6.9 ft., with a healed
blaze.
and new bearing trees
A chinquapin, 5" dia., bears S.33°W., 11.8 ft., mkd. X BT
A fir, 8" dia., bears N.16¾°W., 7.3 ft., mkd. T26S R7W
S21 BT.
Corner is located East of a mound of stone 3 ft. base, 2 ft.
high, erected by Zirpel and Martin
Each new bearing tree has a 2½" X ¼" Magnetic nail (MAG-NAIL)
driven at the base right side-center, unless otherwise
described in the corner description

Fd. as per record by K Hoffine, 3/2016 - M170-67