

TOWNSHIP 26 RANGE 07 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Under Contract #57 dated April 12, 1855 (DCSO records, Volume 11 Page 4611)

-----  
Set 1/4 sec. post, from which  
    A Fir 12" dia., bears N.72°E., 26 lks. dist.  
    A Hemlock 10" dia., bears S.20°W., 10 lks. dist.

-----  
Bureau of Land Management resurvey by Peterson, etal, under Group #'s 744 and 838. Survey May 1971-Aug. 1974 (DCSO records, Volume 37 Page 15174)

-----  
Point for the 1/4 cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an Iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T 26 S R 7 W

1/4

S 21 | S 22

1974

from which

    A Fir 8" dia., bears S.32°E., 86 lks. dist. mkd.  
        1/4 S22 BT.

    A Fir 9" dia., bears S.40°W., 95 1/2 lks. dist. mkd.  
        1/4 S21 BT.

The corner is located at bottom of descent, slopes S.75°E.

-----  
Fd. Ok - Jan 1994 - by Harold Stockhoff - M 118 -23

-----  
Fd. ok by BLM Dependent resurvey by Timothy J. Moore, Cad. Surveyor & Robert Browning, Surveying Technician under Group #1990, surveyed 2001/2002 (DCSO rec. Vol. 54 pg(s) 21013)